

# 屋内照明器具特性

|         |                        |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XLGB1696               |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LLD2000CU1 x1 566.0 lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0179045(0)DR1         |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ5/0.9/BZ4            |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                 |         |                 |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|--------|-----------------|---------|-----------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 94%             | 天井      | 80%             |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |
|        |                 | 壁       | 70              | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |     |
| 上方光束   | 1%              | 床       | 10%             |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |     |
| 下方光束   | 93%             | 室指数     | 照明率 (X0.01) ZCM |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
| 保守率    | 良               | 0.67    | 0.6             | 5.4 | 4.2 | 3.5 | 3.0 | 5.2 | 4.2 | 3.5 | 3.0 | 5.0 | 4.1 | 3.4 | 3.0 | 4.8 | 4.0 | 3.4 | 3.0 | 2.8 |
|        | 中               | 0.63    | 0.8             | 6.3 | 5.3 | 4.6 | 4.0 | 6.2 | 5.2 | 4.5 | 4.0 | 5.9 | 5.1 | 4.5 | 4.0 | 5.7 | 5.0 | 4.4 | 4.0 | 3.8 |
|        | 否               | 0.56    | 1.0             | 7.0 | 6.0 | 5.3 | 4.8 | 6.8 | 5.9 | 5.3 | 4.8 | 6.6 | 5.8 | 5.2 | 4.7 | 6.3 | 5.6 | 5.1 | 4.7 | 4.5 |
|        |                 |         | 1.25            | 7.6 | 6.7 | 6.0 | 5.5 | 7.4 | 6.6 | 6.0 | 5.5 | 7.1 | 6.4 | 5.9 | 5.5 | 6.9 | 6.3 | 5.8 | 5.4 | 5.2 |
| 下方投影面積 | cm <sup>2</sup> |         | 1.5             | 8.0 | 7.2 | 6.6 | 6.1 | 7.8 | 7.1 | 6.5 | 6.0 | 7.5 | 6.9 | 6.4 | 6.0 | 7.3 | 6.7 | 6.3 | 5.9 | 5.7 |
| 等価発光面積 | cm <sup>2</sup> |         | 2.0             | 8.5 | 7.9 | 7.3 | 6.9 | 8.3 | 7.8 | 7.3 | 6.9 | 8.1 | 7.6 | 7.1 | 6.8 | 7.8 | 7.4 | 7.0 | 6.7 | 6.5 |
| 取付高さ   | 器具間隔最大限         |         | 2.5             | 8.8 | 8.3 | 7.8 | 7.4 | 8.7 | 8.2 | 7.8 | 7.4 | 8.4 | 8.0 | 7.6 | 7.3 | 8.2 | 7.8 | 7.5 | 7.2 | 7.0 |
|        | 横方向 (A)         | 縦方向 (B) | 3.0             | 9.0 | 8.6 | 8.2 | 7.8 | 8.9 | 8.5 | 8.1 | 7.8 | 8.6 | 8.3 | 8.0 | 7.7 | 8.4 | 8.1 | 7.8 | 7.6 | 7.3 |
| Hm     | 1.29Hm          | 1.29Hm  | 4.0             | 9.3 | 9.0 | 8.6 | 8.4 | 9.2 | 8.9 | 8.6 | 8.3 | 8.9 | 8.6 | 8.4 | 8.2 | 8.7 | 8.5 | 8.2 | 8.0 | 7.8 |
|        |                 |         | 5.0             | 9.5 | 9.2 | 8.9 | 8.7 | 9.4 | 9.1 | 8.8 | 8.6 | 9.1 | 8.9 | 8.7 | 8.5 | 8.9 | 8.7 | 8.5 | 8.3 | 8.1 |
|        |                 |         | 7.0             | 9.7 | 9.5 | 9.3 | 9.1 | 9.5 | 9.3 | 9.2 | 9.0 | 9.3 | 9.1 | 9.0 | 8.8 | 9.1 | 8.9 | 8.8 | 8.7 | 8.4 |
|        |                 |         | 10.0            | 9.8 | 9.7 | 9.5 | 9.4 | 9.7 | 9.5 | 9.4 | 9.3 | 9.5 | 9.3 | 9.2 | 9.1 | 9.2 | 9.1 | 9.0 | 8.9 | 8.7 |

