

# 屋内照明器具特性

品番 (品名)	XF X4 6 4 NHW														
光源	LED4000_85_5710 x1 5710.0 lm														
管理番号	K0193781(0)DB1														
BZ分類	BZ4/6.0/BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	11%	反射率	床	10%				10%				10%				10%				0%
下方光束	89%		室指数	照明率 ( X0.01) ZCM																
保守率	良 0.83 中 0.81 否 0.77	0.6	58	47	40	35	56	46	39	34	53	44	38	33	50	42	37	33	30	
		0.8	68	57	50	45	66	56	49	44	62	54	48	43	59	52	46	42	39	
		1.0	74	65	57	52	72	63	57	52	68	60	55	50	64	58	53	49	46	
		1.25	80	71	64	59	78	69	63	58	73	66	61	57	69	64	59	55	52	
下方投影面積	c m <sup>2</sup>	1.5	84	76	69	64	81	74	68	63	77	71	66	62	73	67	63	60	56	
		2.0	89	82	76	72	86	80	75	71	82	76	72	69	77	73	69	66	62	
取付高さ	器具間隔最大限		2.5	92	86	81	77	89	84	80	76	85	80	76	73	80	77	74	71	66
	横方向 (A)	縦方向 (B)	3.0	94	89	85	81	92	87	83	79	87	83	80	77	82	79	76	74	69
1.5m	1.92m	2.04m	4.0	97	93	89	86	94	91	87	84	90	87	84	81	85	83	80	78	73
2	2.54	2.58	5.0	98	95	92	89	96	93	90	87	91	89	86	84	87	85	83	81	76
2.5	3.17	3.14	7.0	100	98	95	93	98	96	93	91	93	91	90	88	89	87	86	84	79
3	3.78	3.72	10.0	102	100	98	97	100	98	96	95	95	93	92	91	91	89	88	87	82

