

屋内照明器具特性

品番 (品名)	XLGB1871														
光源	LLD2000CU1 x1 566.0 lm														
管理番号	K0190104(1)DR1														
BZ分類	BZ3														

器具効率	72 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	1 %																			
下方光束	71 %																			
室指数	照明率 (X0.01) ZCM																			
保守率	良 0.67 中 0.63 否 0.56	0.6	46	38	33	30	45	38	33	30	43	37	33	30	42	36	32	30	28	
		0.8	53	46	42	38	52	46	41	38	50	45	41	38	49	44	40	38	36	
		1.0	58	52	47	44	57	51	47	44	55	50	46	43	53	49	46	43	42	
		1.25	61	56	52	49	60	55	52	49	59	54	51	48	57	53	50	48	46	
下方投影面積	c m ²	1.5	64	59	55	52	63	58	55	52	61	57	54	52	59	56	53	51	50	
		2.0	67	63	60	57	66	62	59	57	64	61	59	56	62	60	58	56	54	
		2.5	69	66	63	61	68	65	62	60	66	64	61	59	64	62	60	59	57	
取付高さ	器具間隔最大限																			
	横方向 (A)	縦方向 (B)																		
H m	1.33 H m	1.33 H m	4.0	72	70	68	66	71	69	67	66	69	68	66	65	68	66	65	64	62
			5.0	73	71	70	68	72	71	69	68	70	69	68	66	69	67	66	65	63
			7.0	74	73	72	70	73	72	71	70	72	71	70	69	70	69	68	67	65
			10.0	75	74	73	72	74	73	73	72	73	72	71	70	71	70	70	69	67

