

屋内照明器具特性

品番 (品名)	XLF436NNN(JYOUJI_CEILING)									
光源	LED5000_85_3070 x1 3070.0 1m									
管理番号	K0153233(4)DB1									
BZ分類	BZ6/0.7/BZ5/3.5/BZ6/4.5/BZ5 /6.0/BZ6									

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	9%	床	10%				10%				10%				10%				0%	
下方光束	91%	室指数	照明率 (X0.01) ZCM																	
保守率	良	0.83	0.6	53	41	33	27	52	40	32	27	48	38	31	26	45	36	30	26	23
	中	0.81	0.8	63	51	42	36	61	50	42	36	57	47	40	35	53	45	39	34	31
	否	0.77	1.0	69	58	50	43	67	56	49	43	63	54	47	42	59	51	45	41	37
			1.25	75	65	57	50	73	63	56	50	68	60	54	48	64	57	52	47	43
下方投影面積	cm ²		1.5	79	69	62	56	77	68	61	55	72	65	58	53	68	62	56	52	48
等価発光面積	cm ²		2.0	85	77	70	64	82	75	68	63	78	71	66	61	73	68	63	59	55
取付高さ	器具間隔最大限		2.5	88	81	75	70	86	79	74	69	81	76	71	67	77	72	68	64	60
	横方向 (A)	縦方向 (B)	3.0	91	85	79	74	89	83	77	73	84	79	74	71	79	75	72	68	64
1.5m	1.97m	2.1m	4.0	94	89	84	80	92	87	83	79	87	83	80	76	83	79	76	74	69
2	2.61	2.67	5.0	96	92	88	84	94	90	86	83	89	86	83	80	85	82	80	77	72
2.5	3.24	3.25	7.0	99	96	92	89	97	93	91	88	92	89	87	85	88	86	84	82	76
3	3.88	3.86	10.0	101	98	96	94	99	96	94	92	94	92	90	89	90	88	87	85	80

