

屋内照明器具特性

品番 (品名)	XF X4 4 8 GE W									
光源	LED4000_85_3450 x1					3450.0 lm				
管理番号	K0192153(0)D 1									
BZ分類	BZ4									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		100%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.81	0.6	5.9	4.7	3.9	3.4	5.7	4.6	3.9	3.4	5.5	4.5	3.8	3.4	5.3	4.4	3.8	3.4	3.2	
	中	0.77	0.8	6.9	5.8	5.1	4.5	6.8	5.7	5.0	4.5	6.5	5.6	5.0	4.5	6.3	5.5	4.9	4.5	4.3	
	否	0.68	1.0	7.6	6.6	5.9	5.3	7.4	6.5	5.8	5.3	7.2	6.4	5.7	5.3	6.9	6.2	5.7	5.2	5.0	
	下方投影面積		1.25	8.2	7.3	6.6	6.1	8.0	7.2	6.6	6.1	7.7	7.0	6.5	6.0	7.5	6.9	6.4	6.0	5.8	
等価発光面積		1.5	8.6	7.8	7.2	6.7	8.4	7.7	7.1	6.6	8.1	7.5	7.0	6.6	7.9	7.3	6.9	6.5	6.3		
		2.0	9.1	8.5	7.9	7.5	9.0	8.4	7.8	7.4	8.7	8.2	7.7	7.3	8.4	8.0	7.6	7.3	7.0		
取付高さ	器具間隔最大限		2.5	9.5	8.9	8.4	8.0	9.3	8.8	8.3	8.0	9.0	8.6	8.2	7.9	8.8	8.4	8.1	7.8	7.5	
	横方向 (A)	縦方向 (B)	3.0	9.7	9.2	8.8	8.4	9.5	9.1	8.7	8.3	9.3	8.9	8.5	8.2	9.0	8.7	8.4	8.1	7.9	
1.5m	2.05m	2.1m	4.0	10.0	9.6	9.2	8.9	9.8	9.5	9.2	8.9	9.6	9.3	9.0	8.7	9.3	9.0	8.8	8.6	8.3	
2	2.71	2.65	5.0	10.1	9.8	9.5	9.3	10.0	9.7	9.4	9.2	9.7	9.5	9.3	9.1	9.5	9.3	9.1	8.9	8.6	
2.5	3.37	3.21	7.0	10.3	10.1	9.9	9.7	10.2	10.0	9.8	9.6	9.9	9.8	9.6	9.4	9.7	9.6	9.4	9.3	9.0	
3	4.03	3.79	10.0	10.5	10.3	10.2	10.0	10.4	10.2	10.1	9.9	10.1	10.0	9.9	9.7	9.9	9.8	9.7	9.6	9.3	

