




非常用照明器具特性



品番	XLF436PNNC(CEILING)		
名称			
光源	LED5000/97/445		
管理番号	K0168486(1)DR1		
光束	8900mm x 1000		
保守率	0.92		
適用品番	設計照度Eを得るための読取照度		
	E=2.0	E=1.0	E=0.5
XLF436PNNC(CEILING)	2.4	1.2	0.6
備考	非常点灯時の照度(60分後)		



品番	XLF436PNNC(CEI LI NG)			
名称				
光源	LED5000/97/445			
管理番号	K0168486(10)DR 1			
光束	890.0 1m * 1.00		備考	非常点灯時の照度 (60分後)
保守率	0.92			

非常灯配置表

器具取付高さ(m)		2.1	2.2	2.3	2.4	2.5	2.6	2.7	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6
単体配置	A1	5.5	5.6	5.7	5.8	5.9	6.0	6.1	6.2	6.3	6.4	6.5	6.6	6.8	6.9	7.0	7.1
	A'1	1.8	1.9	1.9	2.0	2.1	2.1	2.2	2.3	2.3	2.4	2.5	2.5	2.6	2.7	2.7	2.8
	B1	3.4	3.4	3.4	3.5	3.5	3.5	3.5	3.6	3.6	3.6	3.6	3.6	3.6	3.7	3.7	3.7
直線配置	A2	7.5	7.7	7.9	8.1	8.3	8.5	8.7	8.9	9.1	9.3	9.5	9.6	9.9	10.0	10.2	10.4
	B2	7.0	7.2	7.5	7.7	8.0	8.2	8.4	8.6	8.8	8.9	9.1	9.2	9.4	9.6	9.6	9.7
四角配置	A4	6.6	6.6	6.8	7.1	7.4	7.3	7.9	7.6	8.1	8.0	8.5	8.2	8.8	8.7	8.9	9.0
	B4	7.0	7.2	7.5	7.7	8.0	8.2	8.2	8.6	8.6	8.9	8.7	9.2	9.0	9.4	9.4	9.6
壁からの距離(最大)	A0	1.0	1.0	1.0	1.0	1.0	1.0	1.1	1.0	1.1	1.0	1.3	1.0	1.3	1.1	1.3	1.3
	B0	2.5	2.8	2.7	2.6	2.6	2.9	2.6	3.0	2.8	3.1	2.7	3.2	2.9	3.2	3.1	3.2

器具取付高さ(m)		3.7	3.8	3.9	4.0	4.1	4.2	4.3	4.4	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0
単体配置	A1	7.2	7.3	7.4	7.5	7.6	7.7	7.7	7.7	7.8	8.0	8.3	8.5	8.7	9.0	9.1	9.2
	A'1	2.8	2.9	3.0	3.0	3.1	3.2	3.2	3.3	3.3	3.6	3.9	4.1	4.4	4.6	4.8	5.0
	B1	3.7	3.7	3.7	3.8	3.8	3.8	3.8	3.8	3.8	3.9	3.9	3.9	3.9	3.9	3.8	3.8
直線配置	A2	10.6	10.8	10.9	11.2	11.4	11.6	11.7	11.9	12.0	12.6	13.2	13.9	14.5	15.1	15.6	16.1
	B2	9.7	9.8	9.8	9.8	9.9	9.9	9.9	10.0	10.0	10.1	10.3	10.5	10.6	10.7	10.8	10.9
四角配置	A4	9.2	9.4	9.6	9.8	10.0	10.2	10.4	10.6	10.8	11.8	12.8	13.7	14.5	15.1	15.6	16.1
	B4	9.6	9.7	9.7	9.8	9.8	9.9	9.9	10.0	10.0	10.1	10.3	10.4	10.5	10.6	10.8	10.8
壁からの距離(最大)	A0	1.3	1.5	1.5	1.6	1.7	1.8	1.8	1.9	2.0	2.3	2.6	2.7	3.0	3.0	2.9	2.0
	B0	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.1	2.9	2.5	2.0	1.4	1.3	1.5	1.1

器具取付高さ(m)		8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	12.5	13.0	13.5	14.0				
単体配置	A1	9.3	9.3	9.3	9.1	8.9	8.6	8.2	7.7	7.1	5.5	2.8	----				
	A'1	5.1	5.2	5.3	5.3	5.2	5.0	3.7	2.9	2.3	1.8	1.5	----				
	B1	3.7	3.7	3.6	3.5	3.4	3.3	3.1	2.9	2.8	2.6	2.1	----				
直線配置	A2	16.6	17.0	17.4	17.7	17.9	18.0	18.1	17.9	17.7	16.7	14.5	12.5				
	B2	10.9	10.8	10.7	10.6	10.4	10.2	9.9	9.6	9.3	9.0	8.8	8.6				
四角配置	A4	16.6	17.0	17.4	17.7	17.9	18.0	18.1	17.9	17.7	16.7	14.5	12.5				
	B4	10.9	10.8	10.7	10.6	10.4	10.2	9.9	9.6	9.3	9.0	8.8	8.6				
壁からの距離(最大)	A0	1.0	1.5	1.3	1.1	1.0	1.1	1.0	1.0	1.0	1.1	1.0	1.0				
	B0	1.3	1.4	1.3	1.2	1.2	1.5	1.2	1.0	1.1	1.2	1.2	1.0				

階段配置表

器具取付高さ(m)			1.0	1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0
Y=1.0(m)	2.0Lx	X+	3.8	4.5	5.2	5.7	6.3	7.3	7.9	8.4	8.8	9.1
		X-	0.9	1.3	1.6	2.0	2.3	2.9	3.5	4.0	4.4	4.7
Y=1.5(m)	1.0Lx	X+	4.9	5.7	6.4	7.1	7.7	8.8	9.8	10.8	11.2	11.7
		X-	0.9	1.2	1.6	1.9	2.3	2.9	3.4	3.8	4.2	4.5
Y=2.0(m)	2.0Lx	X+	3.4	4.1	4.7	5.3	5.9	6.9	7.6	8.1	8.5	8.8
		X-	0.6	1.1	1.5	1.8	2.2	2.7	3.2	3.7	4.0	4.3
	1.0Lx	X+	4.5	5.4	6.1	6.7	7.4	8.5	9.5	10.5	11.0	11.5