

屋内照明器具特性	
品番 (品名)	X F X 4 3 6 Z E N
光源	LED5000_85_2640 ×1 2640.0 l m
管理番号	K0192927 (0) DB 1
B Z 分類	B Z 4

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %							
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %			
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																				Z C M				
下方光束				1 0 0 %																								
保守率		良 中 否	0 . 7 7	0 . 6	5 9	4 7	3 9	3 4	5 8	4 6	3 9	3 4	5 5	4 5	3 9	3 4	5 3	4 4	3 8	3 4	3 2							
			0 . 7 2	0 . 8	6 9	5 8	5 1	4 6	6 8	5 8	5 1	4 5	6 5	5 6	5 0	4 5	6 3	5 5	4 9	4 5	4 3							
			0 . 6 8	1 . 0	7 6	6 6	5 9	5 4	7 5	6 5	5 9	5 3	7 2	6 4	5 8	5 3	6 9	6 2	5 7	5 3	5 1							
				1 . 2 5	8 2	7 3	6 7	6 2	8 1	7 2	6 6	6 1	7 8	7 1	6 5	6 1	7 5	6 9	6 4	6 0	5 8							
下方投影面積		c m ²	1 . 5	8 6	7 8	7 2	6 7	8 5	7 7	7 2	6 7	8 2	7 6	7 1	6 6	7 9	7 4	6 9	6 6	6 4								
			2 . 0	9 2	8 5	8 0	7 6	9 0	8 4	7 9	7 5	8 7	8 2	7 8	7 4	8 5	8 0	7 7	7 4	7 1								
等価発光面積		c m ²	2 . 5	9 5	9 0	8 5	8 1	9 4	8 9	8 4	8 1	9 1	8 7	8 3	8 0	8 8	8 5	8 1	7 9	7 6								
			3 . 0	9 7	9 3	8 9	8 5	9 6	9 2	8 8	8 4	9 3	8 9	8 6	8 3	9 1	8 8	8 5	8 2	8 0								
1 . 5 m	1 . 9 4 m	2 . 1 3 m	4 . 0	1 0 0	9 6	9 3	9 0	9 9	9 5	9 2	9 0	9 6	9 3	9 1	8 8	9 4	9 1	8 9	8 7	8 4								
2	2 . 5 7	2 . 6 8	5 . 0	1 0 2	9 9	9 6	9 4	1 0 0	9 8	9 5	9 3	9 8	9 6	9 3	9 1	9 5	9 3	9 2	9 0	8 7								
2 . 5	3 . 2	3 . 2 6	7 . 0	1 0 4	1 0 1	9 9	9 8	1 0 2	1 0 0	9 8	9 7	1 0 0	9 8	9 7	9 5	9 7	9 6	9 5	9 3	9 1								
3	3 . 8 2	3 . 8 5	1 0 . 0	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 3								

