

# 屋内照明器具特性

品番 (品名)	XLF443HTNJ ( J YOUJ I )																
光源	LED5000_85_3060 ×1 3060.0 1 m																
管理番号	K0153357 ( 0 ) DR 1																
BZ分類	BZ9																

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	50 %	室指数	照明率 ( X0.01 )																	ZCM	
下方光束	50 %																				
保守率	良	0.83	0.6	4.4	3.1	2.3	1.7	4.0	2.9	2.1	1.6	3.2	2.4	1.7	1.3	2.6	1.9	1.4	1.0	0.5	
	中	0.81	0.8	5.2	3.9	3.1	2.5	4.7	3.6	2.8	2.3	3.9	3.0	2.4	1.9	3.1	2.4	1.9	1.5	0.8	
	否	0.77	1.0	5.8	4.6	3.7	3.1	5.3	4.2	3.4	2.8	4.3	3.5	2.8	2.4	3.4	2.8	2.3	1.9	1.1	
			0.77	1.25	6.3	5.2	4.3	3.7	5.8	4.8	4.0	3.4	4.7	4.0	3.3	2.8	3.8	3.2	2.7	2.3	1.4
下方投影面積		cm <sup>2</sup>	1.5	6.8	5.7	4.9	4.2	6.2	5.2	4.5	3.9	5.1	4.3	3.8	3.3	4.1	3.5	3.0	2.7	1.6	
等価発光面積		cm <sup>2</sup>	2.0	7.3	6.4	5.6	5.0	6.7	5.9	5.2	4.6	5.6	4.9	4.4	3.9	4.5	4.0	3.6	3.2	2.1	
取付高さ	器具間隔最大限		2.5	7.7	6.9	6.2	5.6	7.1	6.3	5.7	5.2	5.9	5.3	4.8	4.4	4.8	4.3	3.9	3.6	2.4	
	横方向 (A)	縦方向 (B)	3.0	8.0	7.2	6.6	6.0	7.3	6.7	6.1	5.6	6.1	5.6	5.2	4.8	5.0	4.6	4.2	3.9	2.6	
1.5m	0	2.13m	4.0	8.3	7.7	7.2	6.7	7.7	7.1	6.6	6.2	6.4	6.0	5.6	5.3	5.3	4.9	4.6	4.4	3.0	
2	0	2.7	5.0	8.6	8.0	7.6	7.1	7.9	7.4	7.0	6.6	6.7	6.3	5.9	5.6	5.5	5.2	4.9	4.7	3.2	
2.5	0	3.3	7.0	8.8	8.4	8.0	7.7	8.2	7.8	7.5	7.1	6.9	6.6	6.4	6.1	5.7	5.5	5.3	5.1	3.6	
3	0	3.91	10.0	9.1	8.8	8.5	8.2	8.4	8.1	7.9	7.6	7.1	6.9	6.7	6.5	5.9	5.8	5.6	5.4	3.9	

