

屋内照明器具特性

品番 (品名)	XLF446HNNC(JYOUJI)															
光源	LED5000_85_3060 x1 3060.0 lm															
管理番号	K0153357(0)DR1															
BZ分類	BZ9															

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	50%	室指数	照明率 (X0.01)																ZCM		
下方光束	50%																				
保守率	良 中 否	0.83	0.6	4.4	3.1	2.3	1.7	4.0	2.9	2.1	1.6	3.2	2.4	1.7	1.3	2.6	1.9	1.4	1.0	0.5	
		0.81	0.8	5.2	3.9	3.1	2.5	4.7	3.6	2.8	2.3	3.9	3.0	2.4	1.9	3.1	2.4	1.9	1.5	0.8	
		0.77	1.0	5.8	4.6	3.7	3.1	5.3	4.2	3.4	2.8	4.3	3.5	2.8	2.4	3.4	2.8	2.3	1.9	1.1	
			1.25	6.3	5.2	4.3	3.7	5.8	4.8	4.0	3.4	4.7	4.0	3.3	2.8	3.8	3.2	2.7	2.3	1.4	
下方投影面積	c m ²	1.5	6.8	5.7	4.9	4.2	6.2	5.2	4.5	3.9	5.1	4.3	3.8	3.3	4.1	3.5	3.0	2.7	1.6		
		2.0	7.3	6.4	5.6	5.0	6.7	5.9	5.2	4.6	5.6	4.9	4.4	3.9	4.5	4.0	3.6	3.2	2.1		
取付高さ	器具間隔最大限		2.5	7.7	6.9	6.2	5.6	7.1	6.3	5.7	5.2	5.9	5.3	4.8	4.4	4.8	4.3	3.9	3.6	2.4	
	横方向 (A)	縦方向 (B)	3.0	8.0	7.2	6.6	6.0	7.3	6.7	6.1	5.6	6.1	5.6	5.2	4.8	5.0	4.6	4.2	3.9	2.6	
1.5m	0	2.13m	4.0	8.3	7.7	7.2	6.7	7.7	7.1	6.6	6.2	6.4	6.0	5.6	5.3	5.3	4.9	4.6	4.4	3.0	
2	0	2.7	5.0	8.6	8.0	7.6	7.1	7.9	7.4	7.0	6.6	6.7	6.3	5.9	5.6	5.5	5.2	4.9	4.7	3.2	
2.5	0	3.3	7.0	8.8	8.4	8.0	7.7	8.2	7.8	7.5	7.1	6.9	6.6	6.4	6.1	5.7	5.5	5.3	5.1	3.6	
3	0	3.91	10.0	9.1	8.8	8.5	8.2	8.4	8.1	7.9	7.6	7.1	6.9	6.7	6.5	5.9	5.8	5.6	5.4	3.9	

