

屋内照明器具特性	
品番 (品名)	SLB15780+SLK22006+SLK290
光源	LLD3421LCB1 ×1 700.0 lm
管理番号	K0193059 (0) DB1
BZ分類	BZ4/0.7/BZ5/3.5/BZ6

器具効率		87 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束		25 %	室指数	照明率 (X0.01) ZCM																	
下方光束		62 %																			
保守率		良 中 否	0.63	0.6	47	37	31	26	45	36	30	26	40	33	28	24	36	30	26	23	20
			0.6	0.8	54	44	38	33	51	42	36	32	46	39	34	30	41	36	31	28	24
			0.56	1.0	59	50	43	38	56	47	42	37	50	43	38	34	45	39	35	32	27
				1.25	63	55	48	43	60	52	46	42	54	48	43	39	48	43	39	36	31
下方投影面積		cm ²		1.5	66	59	53	48	63	56	50	46	57	51	46	43	51	46	42	39	33
等価発光面積			cm ²	2.0	71	64	59	54	67	61	56	52	61	56	52	48	54	50	47	44	38
取付 高さ	器具間隔最大限		2.5	74	68	63	58	70	65	60	56	63	59	55	52	57	53	50	48	41	
	横方向 (A) 縦方向 (B)			3.0	76	70	66	62	72	67	63	59	65	61	58	55	58	55	53	50	43
H m	0.49 H m 0.49 H m		4.0	78	74	70	67	75	71	67	64	67	64	61	59	61	58	56	54	46	
			5.0	80	76	73	70	76	73	70	67	69	66	64	62	62	60	58	56	48	
			7.0	82	79	77	74	78	76	73	71	71	69	67	65	64	63	61	60	51	
			10.0	84	82	80	78	80	78	76	74	73	71	70	68	66	65	63	62	53	

