

屋内照明器具特性	
品番 (品名)	SLB15780+SLK22006+SLK290
光源	LLD2411LCB1 ×1 500.0 lm
管理番号	K0193688 (0) DB1
BZ分類	BZ1/0.9/BZ2/2.3/BZ3/8.5/BZ4

器具効率		92 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z CM
保守率		良 中 否	0.63	0.6	65	57	52	49	64	57	52	48	61	55	51	48	59	54	50	47	45
			0.6	0.8	71	64	59	55	70	63	58	55	67	61	57	54	64	59	56	53	50
			0.56	1.0	75	68	63	60	74	67	63	59	70	65	61	58	67	63	59	57	54
				1.25	79	73	68	64	77	71	67	63	74	69	65	62	70	66	63	61	58
下方投影面積		cm ²		1.5	82	76	71	68	80	74	70	67	76	72	68	65	73	69	66	63	60
			等価発光面積	cm ²	2.0	85	80	76	73	83	79	75	72	79	75	72	70	76	72	70	68
取付 高さ	器具間隔最大限			2.5	87	83	79	76	85	81	78	75	81	78	75	73	77	75	72	70	66
	横方向 (A) 縦方向 (B)			3.0	89	85	82	79	87	83	80	78	83	80	77	75	79	77	74	73	68
H m	0.82 H m 0.86 H m			4.0	91	88	85	82	89	86	83	81	85	82	80	78	81	79	77	76	71
				5.0	92	89	87	85	90	88	85	83	86	84	82	80	82	80	79	77	73
				7.0	94	92	90	88	91	90	88	86	87	86	84	83	83	82	81	80	75
				10.0	95	93	92	90	93	91	90	89	88	87	86	85	84	84	83	82	77

