

屋内照明器具特性	
品番 (品名)	X F L 3 2 3 G A
光源	LDL40S. N/ 14 / 26 (2600A) ×2 2600.0 l m
管理番号	K0126764 (1) DR 1
BZ分類	BZ4

器具効率		81 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束		0 %		床	10 %				10 %				10 %				10 %				0 %	
下方光束		81 %		室指数	照明率 (X0.01)																	Z C M
保守率		良 中 否	0.81	0.6	48	38	32	28	47	38	32	28	45	37	31	28	43	36	31	28	26	
			0.77	0.8	56	47	41	37	55	47	41	37	53	46	40	36	51	45	40	36	35	
			0.68	1.0	61	53	47	43	60	53	47	43	58	51	47	43	56	50	46	42	41	
				1.25	66	59	53	49	65	58	53	49	63	57	52	49	60	56	52	48	47	
下方投影面積		cm ²	1.5	69	63	58	54	68	62	57	53	66	61	56	53	64	59	56	53	51		
等価発光面積		cm ²	2.0	74	68	64	60	72	67	63	60	70	66	62	59	68	64	61	59	57		
取付 高さ	器具間隔最大限		2.5	76	72	68	65	75	71	67	64	73	69	66	63	71	68	65	63	61		
	横方向 (A)		縦方向 (B)	3.0	78	74	71	68	77	73	70	67	75	72	69	66	73	70	68	66	64	
1.5m	2.09 m	2.15 m	4.0	81	77	75	72	79	76	74	72	77	75	73	71	75	73	71	69	67		
2	2.78	2.71	5.0	82	79	77	75	81	78	76	74	79	77	75	73	77	75	73	72	70		
2.5	3.46	3.3	7.0	83	82	80	78	82	81	79	77	80	79	77	76	78	77	76	75	73		
3	4.14	3.9	10.0	85	83	82	81	84	82	81	80	82	81	80	79	80	79	78	77	75		

