

屋内照明器具特性	
品番 (品名)	X F L 3 2 6 C B
光源	LDL40S. N / 14 / 26 (2 6 0 0 A) × 2 2 6 0 0 . 0 l m
管理番号	K 0 1 2 6 7 6 6 (1) D R 1
B Z 分類	B Z 4

器具効率		8 7 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		8 7 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 8 1	0 . 6	5 2	4 2	3 5	3 1	5 1	4 1	3 5	3 1	4 9	4 0	3 5	3 1	4 7	3 9	3 4	3 0	2 9	
			0 . 7 7	0 . 8	6 1	5 2	4 5	4 1	6 0	5 1	4 5	4 1	5 7	5 0	4 4	4 0	5 5	4 9	4 4	4 0	3 8	
			0 . 6 8	1 . 0	6 7	5 8	5 2	4 8	6 6	5 8	5 2	4 7	6 3	5 6	5 1	4 7	6 1	5 5	5 1	4 7	4 5	
				1 . 2 5	7 2	6 4	5 9	5 4	7 1	6 4	5 8	5 4	6 8	6 2	5 7	5 4	6 6	6 1	5 7	5 3	5 1	
下方投影面積		c m ²	1 . 5	7 5	6 9	6 3	5 9	7 4	6 8	6 3	5 9	7 2	6 6	6 2	5 8	6 9	6 5	6 1	5 8	5 6		
等価発光面積		c m ²	2 . 0	8 0	7 4	7 0	6 6	7 9	7 3	6 9	6 6	7 6	7 2	6 8	6 5	7 4	7 0	6 7	6 4	6 2		
取付 高さ	器具間隔最大限		2 . 5	8 3	7 8	7 4	7 1	8 1	7 7	7 3	7 0	7 9	7 5	7 2	6 9	7 7	7 4	7 1	6 8	6 6		
	横方向 (A) 縦方向 (B)		3 . 0	8 5	8 1	7 7	7 4	8 3	8 0	7 6	7 3	8 1	7 8	7 5	7 2	7 9	7 6	7 4	7 1	6 9		
1 . 5m	2 . 0 7 m	2 . 0 5 m	4 . 0	8 7	8 4	8 1	7 8	8 6	8 3	8 0	7 8	8 3	8 1	7 9	7 7	8 1	7 9	7 7	7 6	7 3		
2	2 . 7 4	2 . 5 7	5 . 0	8 8	8 6	8 3	8 1	8 7	8 5	8 3	8 1	8 5	8 3	8 1	7 9	8 3	8 1	8 0	7 8	7 6		
2 . 5	3 . 4 1	3 . 1	7 . 0	9 0	8 8	8 6	8 5	8 9	8 7	8 5	8 4	8 7	8 5	8 4	8 2	8 5	8 3	8 2	8 1	7 9		
3	4 . 0 8	3 . 6 5	1 0 . 0	9 1	9 0	8 9	8 7	9 0	8 9	8 8	8 7	8 8	8 7	8 6	8 5	8 6	8 5	8 4	8 3	8 1		

