

屋内照明器具特性

品番 (品名)	XLJ 4 2 0 0 J									
光源	LED5000_92_6100 x1 6100.0 1 m									
管理番号	K0173856 (0) DY 1									
BZ分類	BZ4 / 0.9 / BZ3									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %																					
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																					
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %																					
下方光束	100 %	室指数	照明率 (X0.01)																ZCM																					
保守率	良	0.9	0.6	59	48	40	35	58	47	40	35	56	46	40	35	54	45	39	35	33																				
	中	0.87	0.8	71	61	54	48	70	60	53	48	67	59	53	48	65	57	52	48	46																				
	否	0.83	1.0	78	69	63	58	77	68	62	57	74	67	61	57	72	66	61	57	55																				
			1.25	85	77	70	66	83	76	70	65	81	74	69	65	78	73	68	65	63																				
下方投影面積			cm ²		1.5		89		81		76		71		87		81		75		71		84		79		74		70		82		77		73		70		68	
等価発光面積			cm ²		2.0		94		88		83		79		92		87		83		79		90		85		81		78		87		83		80		77		75	
取付高さ	器具間隔最大限		2.5		97		92		88		84		95		91		87		84		93		89		86		83		90		87		84		82		80			
	横方向 (A)	縦方向 (B)	3.0		99		95		91		88		97		94		90		87		95		92		89		86		92		90		87		85		83			
H _m	1.66H _m	1.66H _m	4.0		101		98		95		93		100		97		94		92		97		95		93		91		95		93		91		89		87			
			5.0		103		100		98		96		101		99		97		95		99		97		95		93		97		95		93		92		89			
			7.0		104		102		101		99		103		101		100		98		101		99		98		96		98		97		96		95		92			
			10.0		106		104		103		102		104		103		102		101		102		101		100		99		100		99		98		97		94			

