

屋内照明器具特性

品番 (品名)	XF X4 5 3 F E W															
光源	LED4000_85_3070 x1 3070.0 1 m															
管理番号	K0192933 (0) DB 1															
B Z 分類	B Z 2															

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %			
上方光束	0 %	室指数	照明率 (X0.01)																Z C M	
下方光束	100 %																			
保守率	良 中 否	0.81	0.6	67	58	51	47	66	57	51	47	64	56	51	47	62	55	50	46	45
		0.77	0.8	78	69	63	59	77	69	63	59	74	67	62	59	72	66	62	58	57
			1.0	84	77	71	67	83	76	71	67	81	75	70	66	79	73	69	66	64
		0.68	1.25	89	83	78	74	88	82	77	74	86	80	76	73	84	79	75	73	71
下方投影面積	c m ²	1.5	92	87	82	78	91	86	81	78	89	84	80	77	87	83	80	77	75	
		2.0	97	92	88	85	95	91	87	84	93	89	86	84	91	88	85	83	81	
取付高さ	器具間隔最大限		2.5	99	95	92	89	98	94	91	88	95	92	90	87	93	91	88	86	84
	横方向 (A)	縦方向 (B)	3.0	101	97	94	92	99	96	94	91	97	94	92	90	95	93	91	89	87
1.5m	1.96 m	1.98 m	4.0	103	100	98	96	101	99	97	95	99	97	95	94	97	95	94	92	90
2	2.61	2.49	5.0	104	102	100	98	103	101	99	97	100	99	97	96	98	97	95	94	92
2.5	3.25	3.02	7.0	105	104	102	101	104	103	101	100	102	100	99	98	99	98	97	94	94
3	3.89	3.55	10.0	106	105	104	103	105	104	103	102	103	102	101	100	100	99	98	96	96

