

屋内照明器具特性	
品番 (品名)	SLB15781+SLK22002+SLK290
光源	LLD3401LCB1 ×1 700.0 lm
管理番号	K0193683 (0) DB1
BZ分類	BZ2/1.8/BZ3/8.5/BZ4

器具効率		9 1 % 上方光束 9 % 下方光束 8 2 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %					
					床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
						照明率 (X 0 . 0 1) Z C M																				
保守率		良 中 否	0 . 6 3	0 . 6	6 0	5 1	4 5	4 1	5 8	5 0	4 5	4 1	5 6	4 9	4 4	4 1	5 3	4 7	4 3	4 0	3 8					
			0 . 6	0 . 8	6 8	6 0	5 4	5 0	6 6	5 9	5 3	4 9	6 3	5 7	5 2	4 9	6 0	5 5	5 1	4 8	4 5					
			0 . 5 6	1 . 0	7 3	6 5	6 0	5 6	7 1	6 4	5 9	5 5	6 8	6 2	5 7	5 4	6 5	6 0	5 6	5 3	5 0					
				1 . 2 5	7 7	7 0	6 5	6 1	7 5	6 9	6 4	6 0	7 2	6 6	6 2	5 9	6 8	6 4	6 1	5 8	5 5					
下方投影面積		c m ²	1 . 5	8 0	7 4	6 9	6 5	7 8	7 2	6 8	6 4	7 4	7 0	6 6	6 3	7 1	6 7	6 4	6 1	5 8						
			2 . 0	8 4	7 9	7 4	7 1	8 2	7 7	7 3	7 0	7 8	7 4	7 1	6 8	7 4	7 1	6 9	6 6	6 3						
取付 高さ	器具間隔最大限		2 . 5	8 6	8 2	7 8	7 5	8 4	8 0	7 7	7 4	8 0	7 7	7 4	7 2	7 7	7 4	7 2	6 9	6 6						
	横方向 (A) 縦方向 (B)		3 . 0	8 8	8 4	8 1	7 8	8 6	8 2	7 9	7 6	8 2	7 9	7 6	7 4	7 8	7 6	7 4	7 2	6 8						
H m	0 . 6 2 H m 0 . 6 2 H m		4 . 0	9 0	8 7	8 4	8 1	8 8	8 5	8 2	8 0	8 4	8 1	7 9	7 7	8 0	7 8	7 6	7 5	7 1						
			5 . 0	9 1	8 9	8 6	8 4	8 9	8 7	8 4	8 2	8 5	8 3	8 1	8 0	8 1	8 0	7 8	7 7	7 2						
			7 . 0	9 3	9 1	8 9	8 7	9 1	8 9	8 7	8 5	8 7	8 5	8 4	8 2	8 3	8 2	8 0	7 9	7 5						
			1 0 . 0	9 4	9 2	9 1	9 0	9 2	9 0	8 9	8 8	8 8	8 7	8 6	8 5	8 4	8 3	8 2	8 1	7 7						

