

屋内照明器具特性	
品番 (品名)	S L B 1 5 7 8 1 + S L K 2 2 0 0 2 + S L K 2 9 0
光源	L L D 3 4 2 1 L C B 1 × 1 7 0 0 . 0 l m
管理番号	K 0 1 9 2 4 8 3 (1) D R 1
B Z 分類	B Z 1

器具効率	5 8 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
			壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
			床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束	5 8 %	室指数	照明率 (X 0 . 0 1)																		Z C M	
下方光束			良	0 . 6 7	0 . 6	5 2	4 9	4 8	4 6	5 2	4 9	4 8	4 6	5 1	4 9	4 7	4 6	5 0	4 9	4 7	4 6	4 6
保守率	中 否	0 . 6 3	0 . 8	5 5	5 2	5 1	5 0	5 4	5 2	5 1	4 9	5 4	5 2	5 0	4 9	5 3	5 1	5 0	4 9	4 9		
		0 . 5 6	1 . 0	5 6	5 4	5 3	5 2	5 6	5 4	5 2	5 1	5 5	5 3	5 2	5 1	5 4	5 3	5 2	5 1	5 0		
		1 . 2 5	5 8	5 6	5 4	5 3	5 7	5 5	5 4	5 3	5 6	5 5	5 4	5 3	5 5	5 4	5 3	5 3	5 2			
下方投影面積	c m ²	1 . 5	5 8	5 7	5 6	5 5	5 8	5 6	5 5	5 4	5 7	5 6	5 5	5 4	5 6	5 5	5 4	5 4	5 3			
		2 . 0	6 0	5 8	5 7	5 6	5 9	5 8	5 7	5 6	5 8	5 7	5 6	5 5	5 7	5 6	5 6	5 5	5 4			
等価発光面積	c m ²	2 . 5	6 0	5 9	5 8	5 7	6 0	5 9	5 8	5 7	5 9	5 8	5 7	5 6	5 8	5 7	5 6	5 6	5 5			
		3 . 0	6 1	6 0	5 9	5 8	6 0	5 9	5 8	5 8	5 9	5 8	5 8	5 7	5 8	5 7	5 7	5 6	5 5			
H m	0 . 3 4 H m	0 . 3 4 H m	4 . 0	6 1	6 0	6 0	5 9	6 1	6 0	5 9	5 9	5 9	5 9	5 8	5 8	5 8	5 8	5 8	5 7	5 6		
			5 . 0	6 1	6 1	6 0	6 0	6 1	6 0	6 0	5 9	6 0	5 9	5 9	5 9	5 9	5 8	5 8	5 8	5 6		
			7 . 0	6 2	6 1	6 1	6 1	6 1	6 1	6 1	6 0	6 0	6 0	5 9	5 9	5 9	5 9	5 8	5 8	5 7		
			1 0 . 0	6 2	6 2	6 2	6 1	6 1	6 1	6 1	6 1	6 0	6 0	6 0	6 0	5 9	5 9	5 9	5 9	5 7		

