

屋内照明器具特性	
品番 (品名)	SLB15780+SLK22005+SLK290
光源	LLD2411LCB1 ×1 500.0 lm
管理番号	K0193061 (0) DB 1
BZ分類	BZ4/0.7/BZ5/3.5/BZ6

器具効率		89 % 上方光束 26 % 下方光束 63 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	48	38	32	27	46	37	31	27	41	34	29	25	37	31	27	24	20
			0.6	0.8	55	46	39	34	53	44	38	33	47	40	35	31	43	37	32	29	25
			0.56	1.0	60	51	45	40	57	49	43	38	51	45	40	36	46	41	37	33	28
			1.25	65	56	50	45	62	54	48	43	55	49	44	40	50	45	41	37	32	
下方投影面積		cm ²	1.5	68	60	54	49	65	58	52	47	58	52	48	44	52	48	44	41	35	
等価発光面積			cm ²	2.0	73	66	60	56	69	63	58	54	62	57	53	50	56	52	49	46	39
取付高さ				器具間隔最大限		2.5	76	70	65	60	72	66	62	58	65	61	57	53	58	55	52
H m		0.60 H m	0.60 H m	3.0	78	72	68	64	74	69	65	61	67	63	59	56	60	57	54	52	44
H m		0.60 H m	0.60 H m	4.0	80	76	72	68	77	73	69	66	69	66	63	61	62	60	58	55	47
				5.0	82	78	75	72	78	75	72	69	71	68	66	63	64	62	60	58	50
				7.0	84	81	78	76	80	78	75	73	73	71	69	67	66	64	63	61	52
				10.0	86	83	81	79	82	80	78	76	75	73	71	70	68	66	65	64	55

