

| 屋内照明器具特性 |  |
|----------|--|
| 品番 (品名)  | XLGB1124                                     |
| 光源       | LLD20001CQ1 ×1                      531.0 lm |
| 管理番号     | K0176313(0)DR1                               |
| BZ分類     | BZ3  |

|        |         |         |               |     |      |     |      |     |      |     |      |     |      |     |      |     |      |     |     |     |
|--------|---------|---------|---------------|-----|------|-----|------|-----|------|-----|------|-----|------|-----|------|-----|------|-----|-----|-----|
| 器具効率   | 85 %    | 天井      | 80 %          |     |      |     | 70 % |     |      |     | 50 % |     |      |     | 30 % |     |      |     | 0 % |     |
|        |         |         | 壁             | 70  | 50   | 30  | 10   | 70  | 50   | 30  | 10   | 70  | 50   | 30  | 10   | 70  | 50   | 30  | 10  | 0 % |
|        |         |         |               | 床   | 10 % |     |      |     | 10 % |     |      |     | 10 % |     |      |     | 10 % |     |     |     |
| 上方光束   | 0 %     | 室指数     | 照明率 ( X0.01 ) |     |      |     |      |     |      |     |      |     |      |     |      |     |      |     | ZCM |     |
| 下方光束   | 85 %    |         |               |     |      |     |      |     |      |     |      |     |      |     |      |     |      |     |     |     |
| 保守率    | 良       | 0.67    | 0.6           | 5.6 | 4.7  | 4.1 | 3.8  | 5.5 | 4.7  | 4.1 | 3.8  | 5.3 | 4.6  | 4.1 | 3.7  | 5.1 | 4.5  | 4.1 | 3.7 | 3.6 |
|        | 中       | 0.63    | 0.8           | 6.4 | 5.6  | 5.0 | 4.7  | 6.3 | 5.5  | 5.0 | 4.6  | 6.1 | 5.4  | 5.0 | 4.6  | 5.9 | 5.3  | 4.9 | 4.6 | 4.5 |
|        | 否       | 0.56    | 1.0           | 6.9 | 6.2  | 5.7 | 5.3  | 6.8 | 6.1  | 5.6 | 5.3  | 6.6 | 6.0  | 5.6 | 5.2  | 6.4 | 5.9  | 5.5 | 5.2 | 5.0 |
|        |         |         | 1.25          | 7.3 | 6.7  | 6.2 | 5.8  | 7.2 | 6.6  | 6.2 | 5.8  | 7.0 | 6.5  | 6.1 | 5.8  | 6.8 | 6.3  | 6.0 | 5.7 | 5.6 |
| 下方投影面積 |         |         | 1.5           | 7.6 | 7.0  | 6.6 | 6.2  | 7.5 | 6.9  | 6.5 | 6.2  | 7.3 | 6.8  | 6.4 | 6.1  | 7.1 | 6.7  | 6.4 | 6.1 | 5.9 |
|        |         |         | 2.0           | 8.0 | 7.5  | 7.1 | 6.8  | 7.9 | 7.4  | 7.1 | 6.8  | 7.6 | 7.3  | 7.0 | 6.7  | 7.4 | 7.1  | 6.9 | 6.6 | 6.4 |
| 取付高さ   | 器具間隔最大限 |         | 2.5           | 8.2 | 7.8  | 7.5 | 7.2  | 8.1 | 7.7  | 7.4 | 7.1  | 7.9 | 7.6  | 7.3 | 7.1  | 7.7 | 7.4  | 7.2 | 7.0 | 6.8 |
|        | 横方向 (A) | 縦方向 (B) | 3.0           | 8.4 | 8.0  | 7.7 | 7.5  | 8.2 | 7.9  | 7.7 | 7.4  | 8.0 | 7.8  | 7.5 | 7.3  | 7.8 | 7.6  | 7.4 | 7.2 | 7.0 |
| Hm     | 1.39Hm  | 1.39Hm  | 4.0           | 8.6 | 8.3  | 8.0 | 7.8  | 8.4 | 8.2  | 8.0 | 7.8  | 8.2 | 8.0  | 7.8 | 7.7  | 8.0 | 7.9  | 7.7 | 7.5 | 7.3 |
|        |         |         | 5.0           | 8.7 | 8.5  | 8.3 | 8.1  | 8.6 | 8.4  | 8.2 | 8.0  | 8.4 | 8.2  | 8.0 | 7.9  | 8.2 | 8.0  | 7.9 | 7.8 | 7.5 |
|        |         |         | 7.0           | 8.8 | 8.7  | 8.5 | 8.4  | 8.7 | 8.6  | 8.4 | 8.3  | 8.5 | 8.4  | 8.3 | 8.1  | 8.3 | 8.2  | 8.1 | 8.0 | 7.8 |
|        |         |         | 10.0          | 8.9 | 8.8  | 8.7 | 8.6  | 8.8 | 8.7  | 8.6 | 8.5  | 8.6 | 8.5  | 8.4 | 8.3  | 8.4 | 8.3  | 8.3 | 8.2 | 8.0 |

