

屋内照明器具特性	
品番 (品名)	XLGB1232
光源	LLD20005CQ1 ×1      531.0 lm
管理番号	K0176313(0)DR1
BZ分類	BZ3

器具効率	85%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	85%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.67	0.6	5.6	4.7	4.1	3.8	5.5	4.7	4.1	3.8	5.3	4.6	4.1	3.7	5.1	4.5	4.1	3.7	3.6
	中	0.63	0.8	6.4	5.6	5.0	4.7	6.3	5.5	5.0	4.6	6.1	5.4	5.0	4.6	5.9	5.3	4.9	4.6	4.5
	否	0.56	1.0	6.9	6.2	5.7	5.3	6.8	6.1	5.6	5.3	6.6	6.0	5.6	5.2	6.4	5.9	5.5	5.2	5.0
			1.25	7.3	6.7	6.2	5.8	7.2	6.6	6.2	5.8	7.0	6.5	6.1	5.8	6.8	6.3	6.0	5.7	5.6
下方投影面積	cm <sup>2</sup>	1.5	7.6	7.0	6.6	6.2	7.5	6.9	6.5	6.2	7.3	6.8	6.4	6.1	7.1	6.7	6.4	6.1	5.9	
		2.0	8.0	7.5	7.1	6.8	7.9	7.4	7.1	6.8	7.6	7.3	7.0	6.7	7.4	7.1	6.9	6.6	6.4	
取付高さ	器具間隔最大限		2.5	8.2	7.8	7.5	7.2	8.1	7.7	7.4	7.1	7.9	7.6	7.3	7.1	7.7	7.4	7.2	7.0	6.8
	横方向 (A)	縦方向 (B)	3.0	8.4	8.0	7.7	7.5	8.2	7.9	7.7	7.4	8.0	7.8	7.5	7.3	7.8	7.6	7.4	7.2	7.0
Hm	1.39Hm	1.39Hm	4.0	8.6	8.3	8.0	7.8	8.4	8.2	8.0	7.8	8.2	8.0	7.8	7.7	8.0	7.9	7.7	7.5	7.3
			5.0	8.7	8.5	8.3	8.1	8.6	8.4	8.2	8.0	8.4	8.2	8.0	7.9	8.2	8.0	7.9	7.8	7.5
			7.0	8.8	8.7	8.5	8.4	8.7	8.6	8.4	8.3	8.5	8.4	8.3	8.1	8.3	8.2	8.1	8.0	7.8
			10.0	8.9	8.8	8.7	8.6	8.8	8.7	8.6	8.5	8.6	8.5	8.4	8.3	8.4	8.3	8.3	8.2	8.0

