

屋内照明器具特性	
品番 (品名)	XLGB1517
光源	LLD40003CQ1 ×1                      845.0 l m
管理番号	K0175669 (1) DR 1
BZ分類	BZ2

器具効率	60 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	1 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	59 %	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.67	0.6	4.2	3.6	3.3	3.0	4.1	3.6	3.3	3.0	4.0	3.5	3.2	3.0	3.9	3.5	3.2	3.0	2.9
	中	0.63	0.8	4.7	4.2	3.8	3.6	4.6	4.1	3.8	3.6	4.5	4.1	3.8	3.6	4.3	4.0	3.7	3.5	3.4
	否	0.56	1.0	5.0	4.6	4.2	4.0	4.9	4.5	4.2	4.0	4.8	4.4	4.1	3.9	4.6	4.3	4.1	3.9	3.8
			1.25	5.3	4.9	4.6	4.3	5.2	4.8	4.5	4.3	5.0	4.7	4.5	4.3	4.9	4.6	4.4	4.2	4.1
下方投影面積		cm <sup>2</sup>	1.5	5.5	5.1	4.8	4.6	5.4	5.1	4.8	4.6	5.2	4.9	4.7	4.5	5.1	4.8	4.6	4.5	4.3
等価発光面積		cm <sup>2</sup>	2.0	5.7	5.4	5.2	5.0	5.6	5.4	5.1	4.9	5.5	5.2	5.0	4.9	5.3	5.1	4.9	4.8	4.6
取付高さ	器具間隔最大限		2.5	5.9	5.6	5.4	5.2	5.8	5.5	5.3	5.2	5.6	5.4	5.2	5.1	5.4	5.3	5.1	5.0	4.8
	横方向 (A)	縦方向 (B)	3.0	6.0	5.8	5.6	5.4	5.9	5.7	5.5	5.3	5.7	5.5	5.4	5.3	5.5	5.4	5.3	5.2	5.0
Hm	1.23Hm	1.23Hm	4.0	6.1	5.9	5.8	5.6	6.0	5.8	5.7	5.6	5.8	5.7	5.6	5.5	5.7	5.6	5.5	5.4	5.2
			5.0	6.2	6.0	5.9	5.8	6.1	6.0	5.8	5.7	5.9	5.8	5.7	5.6	5.7	5.7	5.6	5.5	5.3
			7.0	6.3	6.2	6.1	6.0	6.2	6.1	6.0	5.9	6.0	5.9	5.8	5.8	5.8	5.8	5.7	5.6	5.4
			10.0	6.3	6.3	6.2	6.1	6.2	6.2	6.1	6.0	6.1	6.0	6.0	5.9	5.9	5.8	5.8	5.8	5.5

