

屋内照明器具特性	
品番 (品名)	XF X4 6 0 VLN
光源	LED5000_85_6370 x1 6370.0 lm
管理番号	K0193760(0)DB1
BZ分類	BZ4

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	100%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	5.9	4.7	3.9	3.4	5.7	4.6	3.9	3.4	5.5	4.5	3.8	3.4	5.3	4.4	3.8	3.4	3.2
	中	0.77	0.8	6.9	5.7	5.0	4.4	6.7	5.7	5.0	4.4	6.4	5.5	4.9	4.4	6.2	5.4	4.8	4.4	4.2
	否	0.68	1.0	7.5	6.5	5.8	5.2	7.4	6.4	5.7	5.2	7.1	6.2	5.6	5.1	6.8	6.1	5.5	5.1	4.9
			1.25	8.1	7.2	6.5	5.9	7.9	7.1	6.4	5.9	7.6	6.9	6.3	5.9	7.4	6.7	6.2	5.8	5.6
下方投影面積			1.5	8.5	7.7	7.0	6.5	8.3	7.6	6.9	6.5	8.0	7.4	6.8	6.4	7.8	7.2	6.7	6.3	6.1
			2.0	9.0	8.3	7.8	7.3	8.9	8.2	7.7	7.3	8.6	8.0	7.6	7.2	8.3	7.8	7.4	7.1	6.9
取付高さ	器具間隔最大限		2.5	9.4	8.8	8.3	7.8	9.2	8.7	8.2	7.8	8.9	8.5	8.1	7.7	8.7	8.3	7.9	7.6	7.4
	横方向 (A)	縦方向 (B)	3.0	9.6	9.1	8.6	8.3	9.5	9.0	8.6	8.2	9.2	8.8	8.4	8.1	8.9	8.6	8.3	8.0	7.7
1.5m	1.92m	2.12m	4.0	9.9	9.5	9.1	8.8	9.8	9.4	9.1	8.7	9.5	9.2	8.9	8.6	9.2	9.0	8.7	8.5	8.2
2	2.54	2.66	5.0	10.1	9.8	9.4	9.2	9.9	9.6	9.4	9.1	9.7	9.4	9.2	9.0	9.4	9.2	9.0	8.8	8.5
2.5	3.16	3.23	7.0	10.3	10.1	9.8	9.6	10.2	9.9	9.7	9.5	9.9	9.7	9.5	9.4	9.7	9.5	9.3	9.2	8.9
3	3.77	3.81	10.0	10.5	10.3	10.1	9.9	10.3	10.2	10.0	9.9	10.1	9.9	9.8	9.7	9.8	9.7	9.6	9.5	9.2

