

屋内照明器具特性	
品番 (品名)	SLB15782+SLK22001+SLK290
光源	LLD3401LCB1 ×1 700.0 lm
管理番号	K0193243 (0) DB 1
BZ分類	BZ3/0.9/BZ4/3.5/BZ5

器具効率		8 2 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 3	0 . 6	4 8	4 0	3 4	3 0	4 7	3 9	3 3	3 0	4 3	3 6	3 2	2 9	4 0	3 5	3 1	2 8	2 5
			0 . 6	0 . 8	5 5	4 7	4 1	3 7	5 3	4 6	4 0	3 6	4 9	4 3	3 9	3 5	4 6	4 1	3 7	3 4	3 1
			0 . 5 6	1 . 0	6 0	5 2	4 7	4 2	5 8	5 1	4 5	4 1	5 3	4 8	4 3	4 0	5 0	4 5	4 1	3 8	3 5
				1 . 2 5	6 4	5 7	5 2	4 7	6 2	5 5	5 0	4 6	5 7	5 2	4 8	4 4	5 3	4 9	4 5	4 2	3 8
下方投影面積		c m ²		1 . 5	6 7	6 0	5 5	5 1	6 4	5 8	5 4	5 0	6 0	5 5	5 1	4 8	5 5	5 1	4 8	4 5	4 1
			等価発光面積	c m ²	2 . 0	7 1	6 5	6 1	5 7	6 8	6 3	5 9	5 6	6 3	5 9	5 6	5 3	5 9	5 5	5 3	5 0
取付高さ	器具間隔最大限			2 . 5	7 3	6 8	6 4	6 1	7 1	6 6	6 3	5 9	6 6	6 2	5 9	5 6	6 1	5 8	5 5	5 3	4 8
	横方向 (A) 縦方向 (B)			3 . 0	7 5	7 1	6 7	6 4	7 2	6 8	6 5	6 2	6 7	6 4	6 1	5 9	6 2	6 0	5 8	5 6	5 0
H m	1 . 0 6 H m	1 . 0 6 H m		4 . 0	7 7	7 4	7 1	6 8	7 5	7 1	6 9	6 6	6 9	6 7	6 5	6 2	6 4	6 2	6 1	5 9	5 3
				5 . 0	7 9	7 6	7 3	7 1	7 6	7 3	7 1	6 9	7 1	6 9	6 7	6 5	6 6	6 4	6 2	6 1	5 5
				7 . 0	8 0	7 8	7 6	7 4	7 8	7 6	7 4	7 2	7 2	7 1	6 9	6 8	6 7	6 6	6 5	6 4	5 7
				1 0 . 0	8 2	8 0	7 8	7 7	7 9	7 7	7 6	7 5	7 4	7 2	7 1	7 0	6 9	6 8	6 7	6 6	5 9

