

| | |
|----------|---|
| 屋内照明器具特性 | |
| 品番 (品名) | XLGE1102 |
| 光源 | LLD4000VCB1 ×1 845.0 1 m |
| 管理番号 | K0176339 (0) DR 1 |
| BZ分類 | BZ3/0.9/BZ2/4.5/BZ3/6.0/BZ2 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|---------|---------|---------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|----|
| 器具効率 | 64 % | 天井 | 80 % | | | | 70 % | | | | 50 % | | | | 30 % | | | | 0 % | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0 % | |
| 上方光束 | 0 % | 床 | 10 % | | | | 10 % | | | | 10 % | | | | 10 % | | | | 0 % | |
| 下方光束 | 64 % | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.63 | 0.6 | 41 | 35 | 30 | 27 | 41 | 34 | 30 | 27 | 39 | 34 | 30 | 27 | 38 | 33 | 30 | 27 | 26 |
| | 中 | 0.6 | 0.8 | 48 | 42 | 38 | 35 | 47 | 42 | 38 | 35 | 46 | 41 | 37 | 35 | 44 | 40 | 37 | 35 | 33 |
| | 否 | 0.56 | 1.0 | 52 | 47 | 43 | 40 | 51 | 46 | 43 | 40 | 50 | 45 | 42 | 40 | 48 | 45 | 42 | 39 | 38 |
| | | | 1.25 | 55 | 51 | 47 | 45 | 55 | 50 | 47 | 44 | 53 | 49 | 46 | 44 | 52 | 48 | 46 | 44 | 43 |
| 下方投影面積 | | | 1.5 | 58 | 54 | 50 | 48 | 57 | 53 | 50 | 47 | 55 | 52 | 49 | 47 | 54 | 51 | 49 | 47 | 45 |
| | | | 2.0 | 61 | 57 | 54 | 52 | 60 | 57 | 54 | 52 | 58 | 55 | 53 | 51 | 57 | 54 | 52 | 51 | 49 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 62 | 59 | 57 | 55 | 61 | 59 | 57 | 55 | 60 | 58 | 56 | 54 | 58 | 56 | 55 | 53 | 52 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 63 | 61 | 59 | 57 | 63 | 60 | 58 | 57 | 61 | 59 | 57 | 56 | 60 | 58 | 57 | 55 | 54 |
| Hm | 1.17Hm | 1.17Hm | 4.0 | 65 | 63 | 61 | 60 | 64 | 62 | 61 | 59 | 62 | 61 | 60 | 58 | 61 | 60 | 59 | 58 | 56 |
| | | | 5.0 | 66 | 64 | 63 | 61 | 65 | 63 | 62 | 61 | 63 | 62 | 61 | 60 | 62 | 61 | 60 | 59 | 58 |
| | | | 7.0 | 67 | 66 | 64 | 64 | 66 | 65 | 64 | 63 | 64 | 63 | 63 | 62 | 63 | 62 | 62 | 61 | 59 |
| | | | 10.0 | 67 | 67 | 66 | 65 | 67 | 66 | 65 | 64 | 65 | 65 | 64 | 63 | 64 | 63 | 63 | 62 | 60 |

