

屋内照明器具特性	
品番 (品名)	SLB15782+SLK22001+SLK290
光源	LLD2421LCB1 ×1 500.0 lm
管理番号	K0193062 (0) DB 1
BZ分類	BZ4/0.7/BZ5/3.5/BZ6

器具効率		87 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		25 %	室指数	照明率 (X0.01)																		Z	C		M
下方光束		62 %																							
保守率		良 中 否	0.63	0.6	47	37	31	27	45	36	30	26	40	33	28	24	36	30	26	23	20				
			0.6	0.8	54	44	38	33	51	43	37	32	46	39	34	30	41	36	31	28	24				
				1.0	59	50	43	38	56	48	42	37	50	43	38	35	45	40	35	32	27				
			0.56	1.25	63	55	48	44	60	52	47	42	54	48	43	39	48	43	39	36	31				
下方投影面積		cm ²		1.5	67	59	53	48	63	56	51	46	57	51	47	43	51	46	43	39	34				
			等価発光面積	cm ²	2.0	71	64	59	54	67	61	56	52	61	56	52	48	54	51	47	44	38			
取付 高さ	器具間隔最大限			2.5	74	68	63	59	70	65	60	56	63	59	55	52	57	53	50	48	41				
	横方向 (A)		縦方向 (B)	3.0	76	71	66	62	72	67	63	60	65	61	58	55	59	56	53	50	43				
H m	0.49 H m		0.49 H m	4.0	79	74	70	67	75	71	67	64	68	65	62	59	61	58	56	54	46				
				5.0	80	76	73	70	76	73	70	67	69	67	64	62	63	60	58	57	48				
				7.0	82	79	77	74	78	76	73	71	71	69	67	65	64	63	61	60	51				
				10.0	84	82	80	78	80	78	76	74	73	71	70	68	66	65	64	62	54				

