

屋内照明器具特性	
品番 (品名)	XLGE5114
光源	LLD4000LCE1 ×1                      845.0 lm
管理番号	K0181605(0)DR1
BZ分類	BZ5/0.9/BZ4/6.0/BZ5/8.5/BZ4

器具効率	60%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	10%				10%				10%				10%				0%	
下方光束	60%		床	10%				10%				10%				10%				0%
		室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.63	0.6	3.4	2.7	2.3	1.9	3.4	2.7	2.2	1.9	3.2	2.6	2.2	1.9	3.1	2.6	2.2	1.9	1.8
	中	0.6	0.8	4.0	3.4	2.9	2.6	3.9	3.3	2.9	2.6	3.8	3.2	2.8	2.5	3.6	3.2	2.8	2.5	2.4
	否	0.56	1.0	4.4	3.8	3.4	3.0	4.3	3.8	3.3	3.0	4.2	3.7	3.3	3.0	4.0	3.6	3.2	3.0	2.8
			1.25	4.8	4.2	3.8	3.5	4.7	4.2	3.8	3.4	4.5	4.1	3.7	3.4	4.3	4.0	3.6	3.4	3.3
下方投影面積			1.5	5.0	4.5	4.1	3.8	4.9	4.5	4.1	3.8	4.7	4.3	4.0	3.7	4.6	4.2	3.9	3.7	3.6
			2.0	5.4	4.9	4.6	4.3	5.3	4.9	4.5	4.3	5.1	4.7	4.5	4.2	4.9	4.6	4.4	4.2	4.0
取付高さ	器具間隔最大限		2.5	5.6	5.2	4.9	4.6	5.5	5.1	4.8	4.6	5.3	5.0	4.8	4.5	5.1	4.9	4.7	4.5	4.3
	横方向 (A)	縦方向 (B)	3.0	5.7	5.4	5.1	4.9	5.6	5.3	5.1	4.8	5.4	5.2	5.0	4.8	5.3	5.1	4.9	4.7	4.6
Hm	1.22Hm	1.22Hm	4.0	5.9	5.6	5.4	5.2	5.8	5.6	5.4	5.2	5.6	5.4	5.3	5.1	5.5	5.3	5.2	5.0	4.9
			5.0	6.0	5.8	5.6	5.4	5.9	5.7	5.5	5.4	5.8	5.6	5.4	5.3	5.6	5.5	5.3	5.2	5.1
			7.0	6.1	6.0	5.8	5.7	6.0	5.9	5.8	5.6	5.9	5.8	5.7	5.6	5.7	5.6	5.5	5.5	5.3
			10.0	6.2	6.1	6.0	5.9	6.1	6.0	5.9	5.9	6.0	5.9	5.8	5.7	5.9	5.8	5.7	5.6	5.5

