

屋内照明器具特性	
品番 (品名)	XAS5521L
光源	LLD5020LCC1 ×1 1085.0 l m
管理番号	K0187901 (0) DR 1
BZ分類	BZ1

器具効率		78 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		0 %	室指数	照明率 (X0.01)																			ZCM
下方光束		78 %																					
保守率		良	0.6	64	59	56	54	64	59	56	54	63	58	56	53	62	58	55	53	53			
		中	0.8	69	65	62	60	69	64	62	59	67	64	61	59	66	63	61	59	58			
		否	0.63	1.0	72	68	66	63	72	68	65	63	70	67	65	63	69	66	64	63	62		
			0.56	1.25	75	71	69	67	74	71	68	67	73	70	68	66	71	69	67	66	65		
下方投影面積		c m ²	1.5	77	74	71	69	76	73	71	69	74	72	70	68	73	71	69	68	67			
等価発光面積			c m ²	2.0	79	76	74	72	78	76	74	72	76	74	73	71	75	73	72	71	69		
取付	器具間隔最大限		2.5	80	78	76	75	79	77	76	74	78	76	75	73	76	75	74	73	71			
高さ	横方向 (A)		縦方向 (B)	3.0	81	79	77	76	80	78	77	76	78	77	76	75	77	76	75	74	72		
H m	0.44 H m	0.44 H m		4.0	82	80	79	78	81	80	78	77	79	78	77	76	78	77	76	75	74		
			5.0	82	81	80	79	82	80	80	79	80	79	78	77	78	78	77	76	74			
			7.0	83	82	81	81	82	81	81	80	81	80	79	79	79	78	78	77	75			
			10.0	84	83	82	82	83	82	82	81	81	81	80	80	79	79	79	78	76			

