

屋内照明器具特性	
品番 (品名)	XLGE8022
光源	LLD2000LCE1 ×1 531.0 lm
管理番号	K0190582(0)DR1
BZ分類	BZ10

器具効率	55%	天井	80%				70%				50%				30%				0%																																							
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																							
		床	10%				10%				10%				10%				0%																																							
上方光束	27%	室指数																			照明率 (×0.01)																			ZCM																		
下方光束	28%																																																									
保守率	良 0.63 中 0.6 否 0.56	0.6	23	16	12	9	21	15	11	8	17	12	9	6	13	9	7	5	2																																							
		0.8	28	21	16	12	25	19	15	11	20	15	12	9	16	12	9	7	4																																							
		1.0	31	24	19	16	28	22	18	14	23	18	15	12	18	14	11	9	5																																							
		1.25	34	28	23	19	31	25	21	17	25	21	17	14	20	17	14	11	6																																							
下方投影面積	cm ²	1.5	36	30	26	22	33	28	23	20	27	23	19	17	21	18	16	13	8																																							
		2.0	39	34	30	26	36	31	27	24	30	26	23	20	24	21	18	16	10																																							
取付高さ	器具間隔最大限		2.5	41	37	33	29	38	34	30	27	31	28	25	23	25	23	21	19	12																																						
	横方向 (A)	縦方向 (B)	3.0	43	39	35	32	39	36	32	29	33	30	27	25	27	24	22	20	13																																						
Hm	0.00Hm	1.73Hm	4.0	45	41	38	35	41	38	35	33	35	32	30	28	28	26	24	23	15																																						
			5.0	46	43	40	38	43	40	37	35	36	34	32	30	29	28	26	25	17																																						
			7.0	48	46	43	41	44	42	40	38	37	36	34	33	31	29	28	27	19																																						
			10.0	49	47	46	44	46	44	42	41	39	37	36	35	32	31	30	29	20																																						

