

屋内照明器具特性	
品番 (品名)	SLB15782+SLK22007+SLK290
光源	LLD2401LCB1 ×1 500.0 lm
管理番号	K0193060 (0) DB1
BZ分類	BZ6

器具効率		82 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
上方光束		25 %	室指数	照明率 (X0.01)																			Z	CM	
下方光束		57 %																							
保守率		良 中 否	0.63	0.6	42	32	26	21	40	31	25	21	35	28	23	19	31	25	21	18	15				
			0.6	0.8	49	39	33	28	46	37	31	27	41	34	29	25	36	31	26	23	19				
			0.56	1.0	54	44	38	33	51	42	36	32	45	38	33	29	40	34	30	27	22				
				1.25	58	50	43	38	55	47	41	37	49	42	38	34	43	38	34	31	26				
下方投影面積		cm ²		1.5	61	53	47	42	58	51	45	41	51	46	41	37	46	41	37	34	28				
等価発光面積			cm ²	2.0	66	59	53	48	62	56	51	46	55	50	46	43	49	45	42	39	32				
取付 高さ	器具間隔最大限			2.5	68	62	57	53	65	59	55	51	58	54	50	46	52	48	45	42	35				
	横方向 (A)		縦方向 (B)	3.0	71	65	60	56	67	62	58	54	60	56	52	49	53	50	47	45	38				
H m	0.94 H m	0.94 H m		4.0	73	69	65	61	70	65	62	59	62	59	56	54	56	53	51	49	41				
				5.0	75	71	68	64	71	68	65	62	64	61	59	56	57	55	53	51	43				
				7.0	77	74	71	69	73	71	68	66	66	64	62	60	59	58	56	54	46				
				10.0	79	76	74	72	75	73	71	69	68	66	65	63	61	60	58	57	48				

