

| 屋内照明器具特性 |                          |
|----------|--------------------------|
| 品番 (品名)  | SLB15782+SLK22007+SLK290 |
| 光源       | LLD2411LCB1 ×1 500.0 lm  |
| 管理番号     | K0193061 ( 0 ) DB 1      |
| BZ分類     | BZ4/0.7/BZ5/3.5/BZ6      |

| 器具効率            |           | 89 %<br><br>上方光束<br>26 %<br>下方光束 | 反射率  | 天井   | 80 %              |      |      |      | 70 % |      |      |      | 50 % |      |      |      | 30 % |      |      |      | 0 %  |
|-----------------|-----------|----------------------------------|------|------|-------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
|                 |           |                                  |      | 壁    | 70                | 50   | 30   | 10   | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10   | 0 %  |
|                 |           |                                  |      | 床    | 10 %              |      |      |      | 10 % |      |      |      | 10 % |      |      |      | 10 % |      |      |      | 0 %  |
|                 |           |                                  |      | 室指数  | 照明率 ( X0.01 ) ZCM |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |
| 保守率             |           | 良<br>中<br>否                      | 0.63 | 0.6  | 0.8               | 1.0  | 1.25 | 1.5  | 2.0  | 2.5  | 3.0  | 4.0  | 5.0  | 6.0  | 7.0  | 8.0  | 9.0  | 10.0 | 12.0 | 15.0 |      |
|                 |           |                                  | 0.6  | 0.8  | 1.0               | 1.25 | 1.5  | 2.0  | 2.5  | 3.0  | 4.0  | 5.0  | 6.0  | 7.0  | 8.0  | 9.0  | 10.0 | 12.0 | 15.0 | 18.0 | 20.0 |
|                 |           |                                  | 0.56 | 0.8  | 1.0               | 1.25 | 1.5  | 2.0  | 2.5  | 3.0  | 4.0  | 5.0  | 6.0  | 7.0  | 8.0  | 9.0  | 10.0 | 12.0 | 15.0 | 18.0 | 20.0 |
|                 |           |                                  | 0.56 | 0.8  | 1.0               | 1.25 | 1.5  | 2.0  | 2.5  | 3.0  | 4.0  | 5.0  | 6.0  | 7.0  | 8.0  | 9.0  | 10.0 | 12.0 | 15.0 | 18.0 | 20.0 |
| 下方投影面積          |           | cm <sup>2</sup>                  | 1.25 | 1.5  | 2.0               | 2.5  | 3.0  | 4.0  | 5.0  | 6.0  | 7.0  | 8.0  | 9.0  | 10.0 | 12.0 | 15.0 | 18.0 | 20.0 | 25.0 | 30.0 |      |
| 等価発光面積          |           |                                  | 1.5  | 2.0  | 2.5               | 3.0  | 4.0  | 5.0  | 6.0  | 7.0  | 8.0  | 9.0  | 10.0 | 12.0 | 15.0 | 18.0 | 20.0 | 25.0 | 30.0 |      |      |
| cm <sup>2</sup> |           |                                  | 2.0  | 2.5  | 3.0               | 4.0  | 5.0  | 6.0  | 7.0  | 8.0  | 9.0  | 10.0 | 12.0 | 15.0 | 18.0 | 20.0 | 25.0 | 30.0 | 35.0 | 40.0 |      |
|                 |           |                                  | 2.5  | 3.0  | 4.0               | 5.0  | 6.0  | 7.0  | 8.0  | 9.0  | 10.0 | 12.0 | 15.0 | 18.0 | 20.0 | 25.0 | 30.0 | 35.0 | 40.0 |      |      |
| 取付高さ            | 器具間隔最大限   |                                  | 2.5  | 3.0  | 4.0               | 5.0  | 6.0  | 7.0  | 8.0  | 9.0  | 10.0 | 12.0 | 15.0 | 18.0 | 20.0 | 25.0 | 30.0 | 35.0 | 40.0 | 45.0 |      |
|                 | 横方向 ( A ) | 縦方向 ( B )                        | 3.0  | 4.0  | 5.0               | 6.0  | 7.0  | 8.0  | 9.0  | 10.0 | 12.0 | 15.0 | 18.0 | 20.0 | 25.0 | 30.0 | 35.0 | 40.0 | 45.0 | 50.0 |      |
| H m             | 0.60 H m  | 0.60 H m                         | 4.0  | 5.0  | 6.0               | 7.0  | 8.0  | 9.0  | 10.0 | 12.0 | 15.0 | 18.0 | 20.0 | 25.0 | 30.0 | 35.0 | 40.0 | 45.0 | 50.0 | 55.0 |      |
|                 |           |                                  | 5.0  | 6.0  | 7.0               | 8.0  | 9.0  | 10.0 | 12.0 | 15.0 | 18.0 | 20.0 | 25.0 | 30.0 | 35.0 | 40.0 | 45.0 | 50.0 | 55.0 | 60.0 |      |
|                 |           |                                  | 7.0  | 8.0  | 9.0               | 10.0 | 12.0 | 15.0 | 18.0 | 20.0 | 25.0 | 30.0 | 35.0 | 40.0 | 45.0 | 50.0 | 55.0 | 60.0 | 65.0 | 70.0 |      |
|                 |           |                                  | 10.0 | 12.0 | 15.0              | 18.0 | 20.0 | 25.0 | 30.0 | 35.0 | 40.0 | 45.0 | 50.0 | 55.0 | 60.0 | 65.0 | 70.0 | 75.0 | 80.0 | 85.0 |      |

