

屋内照明器具特性	
品番 (品名)	S L B 1 5 7 8 2 + S L K 2 2 0 0 9
光源	L L D 2 4 2 1 L C B 1 × 1 5 0 0 . 0 l m
管理番号	K 0 1 9 3 0 0 0 (0) D B 1
B Z 分類	B Z 1

器具効率		9 7 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		9 7 %																				
保守率		良 中 否	0 . 6 7	0 . 6	8 1	7 5	7 2	6 9	8 0	7 5	7 2	6 9	7 9	7 4	7 1	6 9	7 8	7 4	7 1	6 9	6 8	
			0 . 6 3	0 . 8	8 7	8 2	7 9	7 6	8 6	8 2	7 8	7 6	8 5	8 1	7 8	7 6	8 4	8 0	7 7	7 5	7 4	
			0 . 5 6	1 . 0	9 1	8 6	8 3	8 1	9 0	8 6	8 3	8 0	8 8	8 5	8 2	8 0	8 7	8 4	8 1	8 0	7 8	
			1 . 2 5	9 4	9 0	8 7	8 4	9 3	8 9	8 6	8 4	9 1	8 8	8 6	8 4	9 0	8 7	8 5	8 3	8 2		
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	9 6	9 2	8 9	8 7	9 5	9 1	8 9	8 7	9 3	9 0	8 8	8 6	9 1	8 9	8 7	8 6	8 4		
			2 . 0	9 8	9 5	9 3	9 1	9 7	9 4	9 2	9 1	9 5	9 3	9 1	9 0	9 3	9 2	9 0	8 9	8 7		
			2 . 5	9 9	9 7	9 5	9 3	9 8	9 6	9 4	9 3	9 6	9 5	9 3	9 2	9 5	9 3	9 2	9 1	8 9		
取付 高さ	器具間隔最大限		3 . 0	1 0 0	9 8	9 7	9 5	9 9	9 7	9 6	9 4	9 7	9 6	9 4	9 3	9 5	9 4	9 3	9 2	9 0		
	横方向 (A)	縦方向 (B)	4 . 0	1 0 1	1 0 0	9 8	9 7	1 0 0	9 9	9 8	9 7	9 8	9 7	9 6	9 5	9 7	9 6	9 5	9 4	9 2		
H m	0 . 4 1 H m	0 . 4 1 H m	5 . 0	1 0 2	1 0 1	1 0 0	9 9	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 7	9 6	9 6	9 5	9 3		
			7 . 0	1 0 3	1 0 2	1 0 1	1 0 0	1 0 2	1 0 1	1 0 0	1 0 0	1 0 0	9 9	9 8	9 8	9 8	9 7	9 7	9 6	9 4		
			1 0 . 0	1 0 3	1 0 3	1 0 2	1 0 2	1 0 2	1 0 2	1 0 1	1 0 1	1 0 0	1 0 0	9 9	9 9	9 8	9 8	9 8	9 7	9 5		

