

屋内照明器具特性	
品番 (品名)	X F X 4 6 9 K E N
光源	LED5000_85_6770 ×1 6770.0 lm
管理番号	K0192151 (0) D 1
BZ分類	BZ5 / 2.8 / BZ4

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		1 %	室指数	照明率 (X0.01)																			Z C M	
下方光束		99 %																						
保守率		良 中 否	0.81	0.6	57	45	37	32	56	44	37	32	53	43	36	31	51	42	36	31	29			
			0.77	0.8	67	56	48	42	66	55	47	42	63	53	47	42	60	52	46	41	39			
			0.68	1.0	74	63	55	50	72	62	55	50	69	61	54	49	66	59	53	49	46			
				1.25	80	70	63	57	78	69	62	57	75	67	61	57	72	66	60	56	54			
下方投影面積		cm ²	1.5	84	75	68	63	82	74	68	63	79	72	67	62	76	70	65	61	59				
			2.0	90	82	76	72	88	81	76	71	85	79	74	70	82	77	73	69	67				
等価発光面積		cm ²	2.5	93	87	82	77	91	86	81	77	88	84	79	76	86	81	78	75	72				
			3.0	96	90	86	82	94	89	85	81	91	87	83	80	88	85	82	79	76				
1.5m		1.94 m	2.11 m	4.0	99	95	91	87	97	93	90	87	94	91	88	85	92	89	86	84				
2		2.56	2.66	5.0	101	97	94	91	99	96	93	90	96	94	91	89	94	91	89	87				
2.5		3.18	3.22	7.0	103	100	98	96	101	99	97	95	99	97	95	93	96	94	93	91				
3		3.8	3.81	10.0	104	103	101	99	103	101	100	98	100	99	98	96	98	97	95	94				

