

屋内照明器具特性	
品番 (品名)	SLB15782+SLK22012+SLK290
光源	LLD3401LCB1 ×1 700.0 lm
管理番号	K0193683 (0) DB1
BZ分類	BZ2/1.8/BZ3/8.5/BZ4

器具効率		91 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	60	51	45	41	58	50	45	41	56	49	44	41	53	47	43	40	38
			0.6	0.8	68	60	54	50	66	59	53	49	63	57	52	49	60	55	51	48	45
			0.56	1.0	73	65	60	56	71	64	59	55	68	62	57	54	65	60	56	53	50
				1.25	77	70	65	61	75	69	64	60	72	66	62	59	68	64	61	58	55
下方投影面積		cm ²		1.5	80	74	69	65	78	72	68	64	74	70	66	63	71	67	64	61	58
				2.0	84	79	74	71	82	77	73	70	78	74	71	68	74	71	69	66	63
等価発光面積		cm ²		2.5	86	82	78	75	84	80	77	74	80	77	74	72	77	74	72	69	66
				3.0	88	84	81	78	86	82	79	76	82	79	76	74	78	76	74	72	68
H m	0.62 H m		0.62 H m	4.0	90	87	84	81	88	85	82	80	84	81	79	77	80	78	76	75	71
				5.0	91	89	86	84	89	87	84	82	85	83	81	80	81	80	78	77	72
				7.0	93	91	89	87	91	89	87	85	87	85	84	82	83	82	80	79	75
				10.0	94	92	91	90	92	90	89	88	88	87	86	85	84	83	82	81	77

