

屋内照明器具特性	
品番 (品名)	SLB15782+SLK22013+SLK290
光源	LLD3401LCB1 ×1 700.0 lm
管理番号	K0193243 (0) DB1
BZ分類	BZ3/0.9/BZ4/3.5/BZ5

器具効率		82 % 上方光束 16 % 下方光束 66 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	48	40	34	30	47	39	33	30	43	36	32	29	40	35	31	28	25
			0.6	0.8	55	47	41	37	53	46	40	36	49	43	39	35	46	41	37	34	31
			0.56	1.0	60	52	47	42	58	51	45	41	53	48	43	40	50	45	41	38	35
				1.25	64	57	52	47	62	55	50	46	57	52	48	44	53	49	45	42	38
下方投影面積		cm ²		1.5	67	60	55	51	64	58	54	50	60	55	51	48	55	51	48	45	41
				2.0	71	65	61	57	68	63	59	56	63	59	56	53	59	55	53	50	45
等価発光面積		cm ²		2.5	73	68	64	61	71	66	63	59	66	62	59	56	61	58	55	53	48
				3.0	75	71	67	64	72	68	65	62	67	64	61	59	62	60	58	56	50
H _m	1.06H _m	1.06H _m		4.0	77	74	71	68	75	71	69	66	69	67	65	62	64	62	61	59	53
				5.0	79	76	73	71	76	73	71	69	71	69	67	65	66	64	62	61	55
				7.0	80	78	76	74	78	76	74	72	72	71	69	68	67	66	65	64	57
				10.0	82	80	78	77	79	77	76	75	74	72	71	70	69	68	67	66	59

