

屋内照明器具特性	
品番 (品名)	X E D 1 1 0 1 L
光源	L L D 2 0 0 0 L C T 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 9 0 4 7 3 (0) D R 1
B Z 分類	B Z 3

器具効率		53 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																	Z C M
下方光束		53 %																			
保守率		良 中 否	0 . 6 3	0 . 6	33	27	23	21	32	27	23	21	31	26	23	21	30	26	23	21	20
			0 . 6	0 . 8	38	33	29	27	37	33	29	27	36	32	29	27	35	31	29	26	25
			0 . 5 6	1 . 0	42	37	34	31	41	37	33	31	40	36	33	31	38	35	33	30	29
			1 . 2 5	45	40	37	35	44	40	37	35	42	39	37	34	41	38	36	34	33	
下方投影面積		c m ²	1 . 5	47	43	40	38	46	42	40	37	44	41	39	37	43	41	38	37	36	
			等価発光面積	c m ²	2 . 0	49	46	44	41	48	46	43	41	47	45	43	41	46	44	42	40
取付 高さ	器具間隔最大限		2 . 5	51	48	46	44	50	48	46	44	49	47	45	43	47	46	44	43	42	
	横方向 (A) 縦方向 (B)		3 . 0	52	49	48	46	51	49	47	46	50	48	46	45	48	47	46	44	43	
H m	1 . 2 1 H m	1 . 2 1 H m	4 . 0	53	51	50	48	52	51	49	48	51	50	48	47	50	49	48	47	45	
			5 . 0	54	52	51	50	53	52	51	49	52	51	50	49	51	50	49	48	47	
			7 . 0	55	54	53	52	54	53	52	51	53	52	51	50	51	51	50	50	48	
			1 0 . 0	55	55	54	53	55	54	53	53	53	53	52	52	52	52	51	51	49	

