

屋内照明器具特性	
品番 (品名)	SLB15783+SLK22000
光源	LLD3401LCB1 ×1 700.0 lm
管理番号	K0193963 (0) DB1
BZ分類	BZ1

器具効率		77 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.67	0.6	55	49	44	41	55	48	44	41	53	48	44	41	52	47	44	41	40
			0.63	0.8	63	57	53	50	62	57	53	50	60	56	52	50	59	55	52	50	48
			0.56	1.0	67	62	58	56	66	62	58	56	65	61	58	55	63	60	57	55	54
				1.25	71	66	63	60	70	66	63	60	68	65	62	60	67	64	61	59	58
下方投影面積		cm ²	1.5	73	69	66	63	72	68	66	63	70	67	65	63	69	66	64	62	61	
			2.0	76	73	70	68	75	72	69	67	73	71	69	67	71	69	68	66	65	
等価発光面積		cm ²	2.5	77	75	72	71	76	74	72	70	75	73	71	69	73	71	70	69	67	
			3.0	78	76	74	72	77	75	74	72	76	74	72	71	74	73	71	70	69	
H m	1.32 H m	1.32 H m	4.0	80	78	76	75	79	77	76	74	77	76	75	73	75	74	73	72	71	
			5.0	80	79	78	77	80	78	77	76	78	77	76	75	76	75	74	74	72	
			7.0	81	80	79	78	80	79	79	78	79	78	77	76	77	76	76	75	73	
			10.0	82	81	81	80	81	80	80	79	79	79	78	78	78	77	77	76	74	

