

屋内照明器具特性	
品番 (品名)	SLB15783+SLK22001+SLK290
光源	LLD3401LCB1 ×1 700.0 lm
管理番号	K0193057 (0) DB1
BZ分類	BZ6

器具効率		81 % 上方光束 25 % 下方光束	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
				室指数	照明率 (X0.01) Z CM																			
保守率		良 中 否	0.63	0.6	41	31	25	20	38	29	24	20	34	27	22	18	30	24	20	17	13			
			0.6	0.8	48	38	31	27	45	36	30	26	40	33	28	24	35	29	25	22	18			
			0.56	1.0	52	43	37	32	49	41	35	30	44	37	32	28	38	33	29	26	21			
				1.25	57	48	42	37	53	46	40	35	47	41	36	32	42	37	33	29	24			
下方投影面積 等価発光面積		cm ² cm ²		1.5	60	52	46	41	56	49	44	39	50	44	40	36	44	39	36	33	27			
				2.0	64	57	52	47	61	54	49	45	54	49	45	41	48	44	40	37	31			
				2.5	67	61	56	51	63	58	53	49	56	52	48	45	50	46	43	41	34			
				3.0	69	64	59	55	65	60	56	52	58	54	51	48	52	49	46	43	36			
H m		0.98 H m		0.98 H m			4.0	72	67	63	60	68	64	60	57	61	58	55	52	54	52	49	47	39
							5.0	73	70	66	63	70	66	63	60	62	60	57	55	56	54	51	50	41
							7.0	75	72	70	67	72	69	66	64	65	62	60	58	58	56	54	53	44
							10.0	77	75	73	71	73	71	69	67	66	65	63	61	59	58	57	56	47

