

屋内照明器具特性	
品番 (品名)	SLB15783+SLK22001+SLK290
光源	LLD3411LCB1 ×1 700.0 lm
管理番号	K0193058 (0) DB 1
BZ分類	BZ5/2.8/BZ6

器具効率		88 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		26 %	室指数	照明率 (X0.01)																	Z	CM
下方光束		62 %																				
保守率		良 中 否	0.63	0.6	47	37	31	26	45	36	30	26	40	33	28	24	36	30	26	23	19	
			0.6	0.8	54	45	38	33	51	43	37	32	46	39	34	30	41	36	31	28	24	
			0.56	1.0	59	50	43	38	56	48	42	37	50	44	38	35	45	40	35	32	27	
				1.25	64	55	49	44	60	53	47	42	54	48	43	39	48	43	39	36	31	
下方投影面積		cm ²		1.5	67	59	53	48	64	56	51	46	57	51	47	43	51	46	43	39	34	
等価発光面積			cm ²	2.0	71	65	59	54	68	62	57	52	61	56	52	48	55	51	47	44	38	
取付 高さ	器具間隔最大限		2.5	74	68	63	59	71	65	61	57	64	59	56	52	57	54	51	48	41		
	横方向 (A) 縦方向 (B)		3.0	76	71	66	62	73	68	64	60	65	62	58	55	59	56	53	51	43		
H m	0.60 H m	0.60 H m	4.0	79	75	71	67	75	71	68	65	68	65	62	59	61	59	56	54	46		
			5.0	81	77	74	71	77	74	71	68	70	67	64	62	63	61	59	57	48		
			7.0	83	80	77	75	79	76	74	72	72	70	68	66	65	63	61	60	51		
			10.0	85	82	80	78	81	79	77	75	73	72	70	69	66	65	64	63	54		

