

屋内照明器具特性	
品番 (品名)	XLGB1692
光源	LLD2000CU1 ×1 566.0 lm
管理番号	K0179094 (0) DR 1
BZ分類	BZ4

器具効率		95 % 上方光束 8 % 下方光束 87 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	55	44	37	32	53	43	37	32	50	42	36	31	48	40	35	31	28
			0.63	0.8	65	55	48	43	63	54	47	42	60	52	46	41	56	50	44	41	38
			0.56	1.0	71	62	55	50	69	61	54	50	66	58	53	49	62	56	51	47	45
				1.25	77	69	62	57	75	67	61	57	71	64	59	55	67	62	58	54	51
下方投影面積 等価発光面積		cm ² cm ²		1.5	81	73	67	63	78	72	66	62	74	69	64	60	71	66	62	59	55
				2.0	86	79	74	70	83	78	73	69	79	74	71	67	75	72	68	65	62
				2.5	89	83	79	75	86	81	77	74	82	78	75	72	78	75	72	70	66
				3.0	91	86	82	78	88	84	80	77	84	81	78	75	80	78	75	73	69
H _m	1.32 H _m	1.32 H _m	4.0	93	89	86	83	91	88	85	82	87	84	82	79	83	81	79	77	72	
			5.0	95	92	89	86	93	90	87	85	88	86	84	82	85	83	81	79	75	
			7.0	97	94	92	90	94	92	90	89	90	89	87	85	86	85	84	82	78	
			10.0	98	96	95	93	96	94	93	91	92	91	89	88	88	87	86	85	80	

