

# 屋内照明器具特性

|         |                |          |
|---------|----------------|----------|
| 品番 (品名) | XLGB1701       |          |
| 光源      | LLD4000VCE1 ×1 | 845.0 lm |
| 管理番号    | K0176189(0)DR1 |          |
| BZ分類    | BZ5            |          |

|        |               |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |
|--------|---------------|---------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
| 器具効率   | 71%           | 天井      | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |    |
|        | 上方光束          |         | 4%   | 反射率 | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0% |
|        | 下方光束          |         | 67%  |     | 床   | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |    |
| 室指数    | 照明率 ( X0.01 ) |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |    |
| 保守率    | 良             | 0.67    | 0.6  | 3.9 | 3.0 | 2.5 | 2.1 | 3.8 | 3.0 | 2.4 | 2.1 | 3.6 | 2.9 | 2.4 | 2.0 | 3.4 | 2.8 | 2.3 | 2.0 | 1.8 |    |
|        | 中             | 0.63    | 0.8  | 4.6 | 3.8 | 3.2 | 2.8 | 4.5 | 3.7 | 3.1 | 2.8 | 4.2 | 3.6 | 3.1 | 2.7 | 4.0 | 3.4 | 3.0 | 2.7 | 2.5 |    |
|        | 否             | 0.56    | 1.0  | 5.1 | 4.3 | 3.7 | 3.3 | 4.9 | 4.2 | 3.7 | 3.3 | 4.7 | 4.0 | 3.6 | 3.2 | 4.4 | 3.9 | 3.5 | 3.1 | 2.9 |    |
|        | 下方投影面積        |         | 1.25 | 5.5 | 4.8 | 4.2 | 3.8 | 5.3 | 4.7 | 4.2 | 3.8 | 5.1 | 4.5 | 4.1 | 3.7 | 4.8 | 4.3 | 3.9 | 3.6 | 3.4 |    |
| 等価発光面積 |               | 1.5     | 5.8  | 5.1 | 4.6 | 4.2 | 5.6 | 5.0 | 4.5 | 4.2 | 5.3 | 4.8 | 4.4 | 4.1 | 5.1 | 4.7 | 4.3 | 4.0 | 3.8 |     |    |
|        |               | 2.0     | 6.2  | 5.6 | 5.2 | 4.8 | 6.0 | 5.5 | 5.1 | 4.8 | 5.7 | 5.3 | 5.0 | 4.6 | 5.5 | 5.1 | 4.8 | 4.5 | 4.3 |     |    |
| 取付高さ   | 器具間隔最大限       |         | 2.5  | 6.4 | 6.0 | 5.6 | 5.2 | 6.3 | 5.9 | 5.5 | 5.2 | 6.0 | 5.6 | 5.3 | 5.0 | 5.7 | 5.4 | 5.2 | 4.9 | 4.7 |    |
|        | 横方向 (A)       | 縦方向 (B) | 3.0  | 6.6 | 6.2 | 5.8 | 5.5 | 6.5 | 6.1 | 5.8 | 5.5 | 6.2 | 5.9 | 5.6 | 5.3 | 5.9 | 5.7 | 5.4 | 5.2 | 4.9 |    |
| Hm     | 1.17Hm        | 1.17Hm  | 4.0  | 6.8 | 6.5 | 6.2 | 6.0 | 6.7 | 6.4 | 6.1 | 5.9 | 6.4 | 6.2 | 5.9 | 5.7 | 6.2 | 6.0 | 5.8 | 5.6 | 5.3 |    |
|        |               |         | 5.0  | 7.0 | 6.7 | 6.5 | 6.2 | 6.8 | 6.6 | 6.4 | 6.2 | 6.6 | 6.4 | 6.2 | 6.0 | 6.3 | 6.1 | 6.0 | 5.8 | 5.5 |    |
|        |               |         | 7.0  | 7.2 | 6.9 | 6.8 | 6.6 | 7.0 | 6.8 | 6.6 | 6.5 | 6.8 | 6.6 | 6.4 | 6.3 | 6.5 | 6.4 | 6.2 | 6.1 | 5.8 |    |
|        |               |         | 10.0 | 7.3 | 7.1 | 7.0 | 6.9 | 7.1 | 7.0 | 6.9 | 6.7 | 6.9 | 6.8 | 6.7 | 6.6 | 6.6 | 6.5 | 6.5 | 6.4 | 6.1 |    |

