

屋内照明器具特性

品番 (品名)	XLGB81907									
光源	LED2700_70_220 x1					220.0 lm				
管理番号	K0169179(0)DR1									
BZ分類	BZ5/0.7/BZ4									

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 50%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				下方光束 50%	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM
保守率	良 中 否 0.63 0.6 0.56	0.6	50	39	32	27	47	37	30	26	39	32	26	23	33	27	23	20	15	
		0.8	60	49	42	37	55	46	39	35	47	40	35	31	39	34	30	27	21	
		1.0	66	56	49	44	61	53	46	42	52	46	41	37	44	39	35	32	25	
		1.25	72	63	56	51	66	59	53	48	57	51	46	43	48	43	40	37	29	
下方投影面積 等価発光面積	c m ²	1.5	75	67	61	56	70	63	58	53	60	55	50	47	50	47	43	41	31	
		2.0	81	74	69	64	75	69	64	60	64	60	56	53	54	51	48	46	35	
取付 高さ	器具間隔最大限		2.5	84	78	73	69	78	73	69	65	67	63	60	57	56	54	51	49	38
	横方向 (A)	縦方向 (B)	3.0	86	81	77	73	80	76	72	69	69	66	63	60	58	56	54	52	39
H m	0.00 H m	1.67 H m	4.0	89	85	82	78	83	79	76	74	71	69	66	64	60	58	57	55	42
			5.0	91	87	84	82	84	82	79	77	73	71	69	67	61	60	59	57	43
			7.0	92	90	88	86	86	84	82	80	74	73	71	70	63	62	61	60	45
			10.0	94	92	91	89	88	86	85	83	76	75	73	72	64	63	63	62	47

