

屋内照明器具特性	
品番 (品名)	XLGB82840
光源	LED5000_70_730 x1 730.0 l m
管理番号	K0169184(0)DR1
BZ分類	BZ5/8.5/BZ6

器具効率	100%	天井	80%				70%				50%				30%				0%
	上方光束 99%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
下方光束	1%	床		10%				10%				10%				10%			
室指数		照明率 ( X0.01 )	ZCM																
保守率	良 0.67	0.6	43	33	26	22	37	28	23	19	25	20	16	13	14	11	9	8	0
	中 0.63	0.8	51	41	34	29	43	35	30	25	30	24	21	18	17	14	12	11	0
	否 0.56	1.0	56	47	40	35	48	41	35	31	33	28	25	22	19	16	14	13	0
		1.25	61	53	47	42	53	46	40	36	36	32	28	26	21	18	17	15	0
下方投影面積	c m <sup>2</sup>	1.5	65	57	51	47	56	49	45	41	38	34	31	29	22	20	18	17	0
		2.0	70	64	58	54	60	55	50	47	41	38	35	33	24	22	21	20	0
取付高さ	器具間隔最大限		2.5	73	68	63	59	63	58	54	51	43	41	38	36	25	24	23	0
	横方向 (A)	縦方向 (B)	3.0	75	70	66	63	65	61	57	54	45	42	40	38	26	25	24	0
H m	1.23 H m	1.32 H m	4.0	78	74	71	68	67	64	61	59	47	45	43	41	27	26	25	0
			5.0	80	76	74	71	69	66	64	62	48	46	45	43	28	27	26	0
			7.0	82	79	77	75	70	69	67	65	49	48	47	46	29	28	28	0
			10.0	83	81	80	78	72	70	69	68	50	49	48	48	29	29	29	0

