

屋内照明器具特性	
品番 (品名)	XLGB82902
光源	LED2700_70_360 ×1 360.0 lm
管理番号	K0171432 (0) DB1
BZ分類	BZ9/0.9/BZ8

器具効率		100 %	反射率	天井	80 %					70 %					50 %					30 %					0 %							
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %							
					床	10 %					10 %					10 %					10 %					0 %						
					室指数	照明率 (X0.01)																				Z CM						
保守率		良 中 否	0.63	0.6	0.56	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	12.0	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	80.0	90.0	100.0
			0.63	0.6	0.56	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	12.0	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	80.0	90.0	100.0
			0.63	0.6	0.56	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	12.0	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	80.0	90.0	100.0
			0.63	0.6	0.56	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	12.0	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	80.0	90.0	100.0
下方投影面積		cm ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	12.0	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	80.0	90.0	100.0	120.0	150.0	200.0	250.0	300.0
等価発光面積		cm ²		2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	12.0	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	80.0	90.0	100.0	120.0	150.0	200.0	250.0	300.0	400.0	500.0
取付高さ	器具間隔最大限			2.5	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	12.0	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	80.0	90.0	100.0	120.0	150.0	200.0	250.0	300.0	400.0	500.0	
	横方向 (A)		縦方向 (B)	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	12.0	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	80.0	90.0	100.0	120.0	150.0	200.0	250.0	300.0	400.0	500.0		
H m	1.59 H m		2.09 H m	4.0	5.0	6.0	7.0	8.0	9.0	10.0	12.0	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	80.0	90.0	100.0	120.0	150.0	200.0	250.0	300.0	400.0	500.0	600.0	700.0	800.0
				5.0	6.0	7.0	8.0	9.0	10.0	12.0	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	80.0	90.0	100.0	120.0	150.0	200.0	250.0	300.0	400.0	500.0	600.0	700.0	800.0	
				7.0	8.0	9.0	10.0	12.0	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	80.0	90.0	100.0	120.0	150.0	200.0	250.0	300.0	400.0	500.0	600.0	700.0	800.0	900.0	1000.0	
				10.0	12.0	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	80.0	90.0	100.0	120.0	150.0	200.0	250.0	300.0	400.0	500.0	600.0	700.0	800.0	900.0	1000.0	1200.0	1500.0	2000.0	

