

屋内照明器具特性	
品番 (品名)	XLGB82915
光源	LED5000_70_190 x1 190.0 l m
管理番号	K0169181 (1) DR 1
BZ分類	BZ5 / 0.7 / BZ4

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	50 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	50 %	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.63	0.6	51	40	32	27	47	37	31	26	40	32	27	23	33	27	23	20	15
	中	0.6	0.8	60	50	42	37	56	46	40	35	47	40	35	32	40	35	31	28	21
	否	0.56	1.0	66	57	50	45	61	53	47	42	52	46	41	38	44	39	36	33	25
			1.25	72	63	57	52	67	59	53	49	57	51	47	43	48	44	41	38	29
下方投影面積	c m <sup>2</sup>		1.5	76	68	62	57	70	64	58	54	60	55	51	48	51	47	44	41	32
	等価発光面積		c m <sup>2</sup>	2.0	81	74	69	65	75	70	65	61	64	60	57	54	54	51	49	47
取付高さ	器具間隔最大限		2.5	84	79	74	70	78	73	69	66	67	63	60	58	57	54	52	50	38
	横方向 (A)	縦方向 (B)	3.0	86	81	77	74	80	76	72	69	69	66	63	61	58	56	54	52	40
H m	0.00 H m	1.64 H m	4.0	89	85	82	79	83	80	77	74	71	69	67	65	60	58	57	56	42
			5.0	91	88	85	82	84	82	79	77	73	71	69	67	61	60	59	58	43
			7.0	93	90	88	86	86	84	82	81	74	73	71	70	63	62	61	60	45
			10.0	94	92	91	89	88	86	85	84	76	74	73	73	64	63	63	62	46

