

屋内照明器具特性

品番 (品名)	XLGE1007	
光源	LLD2000LCB1 ×1	531.0 lm
管理番号	K0176341(0)DR1	
BZ分類	BZ3/0.9/BZ2/4.5/BZ3/6.0/BZ2	

器具効率	68%	天井	80%				70%				50%				30%				0%	
	上方光束		0%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
下方光束	68%	床	10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56
下方投影面積	cm ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0
	等価発光面積	cm ²	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0
取付高さ	器具間隔最大限		2.5	3.0	4.0	5.0	7.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0
	横方向 (A)	縦方向 (B)	1.17H _m	1.17H _m	1.17H _m	1.17H _m	1.17H _m	1.17H _m	1.17H _m	1.17H _m	1.17H _m	1.17H _m	1.17H _m	1.17H _m	1.17H _m	1.17H _m	1.17H _m	1.17H _m	1.17H _m	1.17H _m

