

屋内照明器具特性

品番 (品名)	XLGE1124	
光源	LLD3020LCB1 ×1	795.0 lm
管理番号	K0176345(0)DR1	
BZ分類	BZ1	

器具効率	89%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
下方光束	89%	床	10%				10%				10%				10%				0%		
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
下方投影面積	cm ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0										
	等価発光面積	cm ²	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0										
取付高さ	器具間隔最大限																				
	横方向 (A)	縦方向 (B)																			
Hm	0.41Hm	0.41Hm																			
			2.5	3.0	4.0	5.0	7.0	10.0													
			92	93	94	94	95	95													
			89	91	92	93	94	94													
			88	89	90	91	92	93													
			87	88	89	90	91	92													
			86	87	88	89	90	91													
			85	86	87	88	89	90													
			84	85	86	87	88	89													
			83	84	85	86	87	88													
			82	83	84	85	86	87													
			81	82	83	84	85	86													
			80	81	82	83	84	85													
			79	80	81	82	83	84													
			78	79	80	81	82	83													
			77	78	79	80	81	82													
			76	77	78	79	80	81													
			75	76	77	78	79	80													
			74	75	76	77	78	79													
			73	74	75	76	77	78													
			72	73	74	75	76	77													
			71	72	73	74	75	76													
			70	71	72	73	74	75													
			69	70	71	72	73	74													
			68	69	70	71	72	73													
			67	68	69	70	71	72													
			66	67	68	69	70	71													
			65	66	67	68	69	70													
			64	65	66	67	68	69													

