

屋内照明器具特性	
品番 (品名)	XLH1560DL
光源	LED3000_85_1280 x1 1280.0lm
管理番号	K0173386 (0) DB1
BZ分類	BZ1

器具効率	100 % 上方光束 0 % 下方光束	天井 壁 床	80 %				70 %				50 %				30 %				0 %	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
			10 %				10 %				10 %				10 %				0 %	
室指数		照明率 (X0.01) ZCM																		
保守率	良 中 否	0.6	87	81	78	75	86	81	78	75	85	80	77	75	84	80	77	75	74	
		0.8	92	88	84	82	92	87	84	82	90	86	84	82	89	86	83	81	80	
		1.0	96	91	88	86	95	91	88	86	93	90	88	86	92	89	87	85	84	
		0.68	1.25	98	95	92	90	97	94	92	90	96	93	91	89	94	92	90	89	87
下方投影面積 等価発光面積	c m ² c m ²	1.5	100	97	94	92	99	96	94	92	97	95	93	91	96	94	92	91	89	
		2.0	102	100	98	96	101	99	97	95	100	98	96	95	98	96	95	94	92	
取付 高さ	器具間隔最大限		2.5	104	101	100	98	103	101	99	98	101	99	98	96	99	98	96	95	94
	横方向 (A)	縦方向 (B)	3.0	104	103	101	100	103	102	100	99	101	100	99	98	100	99	98	97	95
H m	0.39 H m	0.70 H m	4.0	105	104	103	102	104	103	102	101	102	101	100	101	100	101	100	99	98
			5.0	106	105	104	103	105	104	103	102	103	102	101	101	101	100	100	99	97
			7.0	107	106	105	105	106	105	104	104	104	103	103	102	102	101	101	100	98
			10.0	107	107	106	106	106	105	105	104	104	103	103	102	102	102	101	101	99

