

屋内照明器具特性	
品番 (品名)	SLB15784+SLK22000+SLK290
光源	LLD3421LCB1 ×1 700.0 lm
管理番号	K0193059 (0) DB 1
BZ分類	BZ4/0.7/BZ5/3.5/BZ6

器具効率		87 % 上方光束 25 % 下方光束 62 %	反射率	天井	80 %					70 %					50 %					30 %					0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %					10 %					10 %					10 %					0 %
					室指数	照明率 (X0.01) ZCM																				
保守率		良 中 否	0.63	0.6	0.6	47	37	31	26	45	36	30	26	40	33	28	24	36	30	26	23	20				
			0.6	0.8	54	44	38	33	51	42	36	32	46	39	34	30	41	36	31	28	24					
			0.56	1.0	59	50	43	38	56	47	42	37	50	43	38	34	45	39	35	32	27					
			0.56	1.25	63	55	48	43	60	52	46	42	54	48	43	39	48	43	39	36	31					
下方投影面積		cm ²	1.5	66	59	53	48	63	56	50	46	57	51	46	43	51	46	42	39	33						
等価発光面積			cm ²	2.0	71	64	59	54	67	61	56	52	61	56	52	48	54	50	47	44	38					
				2.5	74	68	63	58	70	65	60	56	63	59	55	52	57	53	50	48	41					
取付高さ	器具間隔最大限			3.0	76	70	66	62	72	67	63	59	65	61	58	55	58	55	53	50	43					
H m	0.49 H m		0.49 H m	4.0	78	74	70	67	75	71	67	64	67	64	61	59	61	58	56	54	46					
				5.0	80	76	73	70	76	73	70	67	69	66	64	62	62	60	58	56	48					
				7.0	82	79	77	74	78	76	73	71	71	69	67	65	64	63	61	60	51					
				10.0	84	82	80	78	80	78	76	74	73	71	70	68	66	65	63	62	53					

