

屋内照明器具特性	
品番 (品名)	SLB15784+SLK22000+SLK290
光源	LLD2411LCB1 ×1 500.0 lm
管理番号	K0193061 (0) DB 1
BZ分類	BZ4/0.7/BZ5/3.5/BZ6

器具効率		89 % 上方光束 26 % 下方光束 63 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	0.6	0.56	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	10.0	
			48	55	60	65	68	73	76	78	80	82	84	86	88	90	92	94	96	98	100
			38	46	51	56	60	66	70	72	76	78	81	83	85	87	89	91	93	95	97
			32	39	45	50	54	59	63	65	69	71	74	77	79	81	83	85	87	89	91
下方投影面積		cm ²	1.25	1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	10.0	12.5	15	20	25	30	40	50	
等価発光面積			cm ²	65	68	73	76	80	82	84	86	88	90	92	94	96	98	100	125	150	
					56	60	66	70	72	76	78	81	83	85	87	89	91	93	95	97	
						50	54	59	63	65	69	71	74	77	79	81	83	85	87	89	91
取付高さ		器具間隔最大限				2.5	3.0	4.0	5.0	6.0	7.0	8.0	10.0	12.5	15	20	25	30	40	50	
		横方向 (A) 縦方向 (B)				78	80	82	84	86	88	90	92	94	96	98	100	125	150	200	250
H m		0.60 H m 0.60 H m		80		82	84	86	88	90	92	94	96	98	100	125	150	200	250	300	400
				82	84	86	88	90	92	94	96	98	100	125	150	200	250	300	400	500	
				84	86	88	90	92	94	96	98	100	125	150	200	250	300	400	500	600	
				86	88	90	92	94	96	98	100	125	150	200	250	300	400	500	600	800	

