

屋内照明器具特性	
品番 (品名)	SLB15784+SLK22000+SLK290
光源	LLD2421LCB1 ×1 500.0 lm
管理番号	K0193062 (0) DB 1
BZ分類	BZ4/0.7/BZ5/3.5/BZ6

器具効率		87 % 上方光束 25 % 下方光束 62 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
				室指数	照明率 (X0.01) ZCM																		
保守率		良 中 否	0.63	0.6	0.56	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6		
			0.63	0.6	0.56	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
			0.63	0.6	0.56	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
			0.63	0.6	0.56	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
下方投影面積		cm ²	1.25	63	55	48	44	60	52	47	42	54	48	43	39	48	43	39	36	31			
等価発光面積			cm ²	1.5	67	59	53	48	63	56	51	46	57	51	47	43	51	46	43	39	34		
					2.0	71	64	59	54	67	61	56	52	61	56	52	48	54	51	47	44	38	
						2.5	74	68	63	59	70	65	60	56	63	59	55	52	57	53	50	48	41
Hm		0.49Hm				0.49Hm	4.0	79	74	70	67	75	71	67	64	68	65	62	59	61	58	56	54
		5.0	80			76	73	70	76	73	70	67	69	67	64	62	63	60	58	57	48		
		7.0	82	79		77	74	78	76	73	71	71	69	67	65	64	63	61	60	51			
		10.0	84	82	80	78	80	78	76	74	73	71	70	68	66	65	64	62	54				

